

TUBING SPECIFICATION SHEET



SG TOP ASSEMBLY P/N: **001-125-2M**
 REVISION: **A**
 DESCRIPTION: **.125C.250R001CATALOG500M**
 CUSTOMER: **CATALOG**
 CUSTOMER P/N: **N/A**
 CUST. REVISION: **N/A**

EXTRUDED TUBING SPECIFICATIONS:

| | | | |
|---------------------|-----------------|----------------------|------------------|
| TUBING PART NUMBER: | 0011252M | REVISION | A |
| INSIDE DIA. | 0.125 | INSIDE DIA. TOL | +/- .005 |
| OUTSIDE DIA. | 0.25 | OUTSIDE DIA. TOL | REF. |
| WALL | 0.0625 | WALL TOL | +/- .004 |
| LENGTH | 500 FT. | LENGTH TOL | +5 FT./-0 |
| COIL DIAMETER | SPOOL | | |
| MATERIAL | R70-001 | MATERIAL DESCRIPTION | 50A |
| COLORANT | N/A | COLORANT DESCRIPTION | N/A |
| PRINT WHEEL P/N | N/A | INK P/N | N/A |

INSPECTION CRITERIA:

UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN INCHES AND TOLERANCES ARE AS LISTED ABOVE.

PACKAGING SPECIFICATIONS:

| | |
|------------------------|--------------------|
| TUBING POLYBAG P/N | P20-031,DBL |
| COILS/PCS. PER POLYBAG | 1 |
| BAGS PER CARTON | 1 |
| CARTON P/N | P01-603 |
| COILS/PCS. PER CARTON | 1 |
| BAG LABEL P/N | 125-2M-700 |
| LABELS PER BAG | 1 |
| CARTON LABEL P/N | 125-2M-701 |
| LABELS PER CARTON | 2 |
| IMPLANT LABEL P/N | N/A |
| INSERT P/N | N/A |

SPECIAL INSTRUCTIONS/NOTES:

Packaging: Shall be free of contamination and foreign material.
 Cleanliness: Product shall be free from foreign material such as dirt and debris.
 Damage: Product shall be free of any gross damage such as splits, abrasions, etc.
 Reference: Router for Manufacturing & Assembly Processing Parameters.
 Reference: Bill of Material for required components.

| | |
|----------------|----------------------------------|
| E.C.O.# | Reason for Issue / Change |
| 10-0409 | NEW PART NUMBER |