



详细配置表

烧瓶规格/产品型号	三角烧瓶 (支)				100ml	250ml	500ml	1000ml	15ml	18ml	20ml	特殊定制	万能	弹簧摇板
	出厂配置	最多配置	出厂配置	最多配置										
SPH-103B 103D	9	4	3	3	9	56	-	-	-	-	-	260x260x80(mm)	380x360x80(mm)	400x380x80(mm)
SPH-100B 100D 100F	4	4	3	3	9	104	-	-	-	-	-	备有不锈钢和ABS工程塑料两种材质选配		
SPH-200B 200D 200F	5	16	4	3	9	120	-	-	-	-	-	根据用户需求可定做		

详细技术参数

产品型号	SPH-103B				SPH-100B				SPH-100D				SPH-200B				SPH-200D				SPH-200F			
	控制方式	PID (微电脑环境扫描微处理芯片)																						
显示方式	LCD (大屏幕液晶双显)																							
循环方式	高速循环式																							
振荡方式	旋转振荡式																							
驱动方式	往复式																							
振荡方式	旋转振荡式																							
环境要求	温度25℃ 湿度20%-90%																							
标准温度范围	室温以上5℃-60℃ 室温以下20℃-60℃ (最低可达4℃)																							
温度精度	±0.1℃																							
温度均匀度	±0.25℃																							
频率范围	30~400	30~600	30~400	30~400	30~600	30~300	30~400	30~400	30~600	30~300	30~400	30~600	30~300	30~400	30~600	30~300								
旋转精度	±1rpm																							
摆幅幅度	Φ25	Φ5/50	Φ25	Φ25	Φ5/50	Φ25	Φ25	Φ25	Φ5/50	Φ25	Φ25	Φ5/50	Φ25	Φ25	Φ5/50	Φ25								
制冷剂	/																							
冷却器	/																							
加热器	150W				400W																			
定时范围	0 500小时/可持续																							
摇板尺寸	260x260				400x370																			
摇板数量	一块																							
净重	31kg				72kg																			
毛重	54kg				94kg																			
内胆尺寸	360x340x280				410x450x300(mm)																			
外型尺寸	440x410x420				610x610x510(mm)																			
包装尺寸	560x530x560				740x710x530(mm)																			
功率	280W				490W																			
内胆材料	全优质进口不锈钢镜面板																							
材料	ABS特种工程塑料																							