

# 膜片式截止阀 DVE



DVE-8-NPT-F-1/4 SA



DVE-8-OD-6



DVE-8-OD-1/4

## 产品特点

- 膜片式截止阀
- 适用于质量等级达到6.0的腐蚀、有毒性气体及混合气体
- 最大工作压力 40 bar
- 有多种进出口形式或右供选择
- 对外界采用金属-金属密封
- 通过高压氧测试
- 人机工程设计

## 技术参数

类型	膜片式
工作压力	DN8, DN13: max. 40 bar DN19: max. 25 bar
材料:	
阀体	不锈钢316L
膜片:	DN 8 不锈钢 1.4571 DN13/19 不锈钢 1.4310
进-出气接口	内螺纹或 不锈钢焊接管
温度范围	-30°C to +60°C
泄漏率	<10 <sup>-8</sup> mbar l/s He
通径尺寸	8, 13, 19 mm
流量	DN 8: c <sub>v</sub> =0.5 DN 13: c <sub>v</sub> =2.5 DN 19: c <sub>v</sub> =5.9



DVE-13-NPT-F-1/2



DVM-13-OD-15



DVE-19-NPT-F-3/4



DVE-19-OD-1

## 订购信息:

### DVE - 13 - NPT F - 1/2

8		13		19	
NPT F 1/4*	- 1/4"-NPT-F	NPT F 1/2	- 1/2"-NPT-F	NPT F 3/4	- 3/4"-NPT-F
NPT F 3/8*	- 3/8"-NPT-F	OD 12	- SS管 12x1 mm	OD ...	- SS管可订制
OD 6*	- SS管 6x1 mm	OD 15	- SS管 15x1 mm		
OD 8*	- SS管 8x1 mm	OD 1/2	- SS管 1/2" male		
OD 10*	- SS管 10x1 mm				
OD 1/4*	- SS管 1/4" male				
OD 3/8*	- SS管 3/8" male				

## 尺寸

