

特征								
流量范围(ml/分钟)	5 to 3250	5 to 5000 *	5 to 5000 *	5 to 3000	5 to 3000 *	50 to 200	20 to 225	5 to 15 (L/min)
重量/盎司(克)	22 (624)	34 (964)	16 (454)	20 (567)	12 (340)	12 (340)	5 (142)	37 (1049)
背压补偿	30/2升	40/2升	10/5升	25/2升	20/2升		20/225毫升	12/10升
内置计时器/时钟	时钟	计时器	计时器	计时器			计时器	时钟
恒定流量	●	●	●	●	●		●	●
程序化设计	●	△	●				●	●
PC-兼容性	●	†					●	●
多管采样	●	●	●	●	●		●	
流量错误显示	●		●	●	●		●	●
RFI/EMI保护	●	●	●	●	●		●	●
UL本质安全认证	●	●	§	●		●	●	
采矿安全与健康认证		●						
符合欧盟ATEX认证标准		●		●			●	
CE认证标志	●	●	●	●	●	●	●	●
压力补偿	●							●
温度补偿	●		●		●			●
电池类型	NiCad	NiCad	Lithium-ion 或碱性电池	NiCad	碱性电池	NiCad	NiMH或NiCad	Lithium-ion
电池检测	●	†	●	●	●	●	●	●
流量5-500ml/min需加低流量套件	●	●	●	●	●	●		

\* 5~500ml/min需低流量适配器  
 △ 仅高端型号  
 † 仅增强型或高端型号  
 § 仅AirChek XR5000型具有锂电池

