

LC150.700.VE100

Prochrom[®] DAC Columns by Novasep

Preparative chromatography columns - optimum performance guaranteed

When placing an order, please include the Novasep code directly on your PO:

Description	Code
LC150.700.VE100	NVS20920
Spare parts	NVS20547


Note: 700: Column Length
VE: Hydraulically Actuated Piston

1 Product description

The **LC150.700.VE100** preparative High Performance Liquid Chromatography (HPLC) column is designed for cGMP operation. Any type of packing material can be used to fill the column provided the proper packing pressure is chosen to avoid destruction of the particles. It can be operated with the most common solvents used in chromatography. The column module is composed of the column itself and its compression system mounted on a stainless steel frame.

MAIN CHARACTERISTICS	
Internal Diameter (mm)	150
Maximum Bed Length (mm)	400
Operating pressure (bar)	100
Weight (kg)	350
Operating Temperature (°C)	5 to 60
Compression feature	Dynamic Axial Compression
Slurry inlets	1
DxWxH (mm)	693 x 704 x 2446

Although Prochrom[®] DAC column can be connected to any pumping system, performance is maximized when used in conjunction with our Prochrom[®] Hipersep chromatography systems.



Pure Performance for the Life Sciences



Product Data Profile

2 Product Specifications

LC150.700.VE100	
ITEM	DESCRIPTION
Column	<p>Column Tube</p> <p>The internal diameter of the column tube is 150 mm. The standard surface roughness of the column tube ID is 0.4 µm (15.7 µ inches). The external finish is approximately 1.6 µm (63 µ inches).</p>
	<p>Piston and Flange</p> <p>The piston and flange of the column contain a woven mesh frit (2µm nominal porosity) and a flow distributor to provide even distribution of the liquid ("plug flow") over the cross section of the packed bed. The finish of the wetted surface roughness of the piston and flange is approximately 0.8µm (30 µ inches)</p> <p>The flange is sealed to the column tube with a FEP encapsulated "O"-ring and held in place with a quick release chain. The piston is sealed to the column tube with a PTFE seal. The other seals are PTFE, FEP encapsulated.</p> <p>The piston's frit is cooled down with liquid nitrogen (or carbon dioxide ice) in order to shrink it. Back at room temperature, the frit expands and fits tightly to its housing.</p>
	<p>Hydraulic Jack</p> <p>The hydraulic jack is mounted above the column tube. The hydraulic jack has a stroke length of 700 mm, which allows the user to pack beds of variable lengths. The hydraulic jack exterior is made of stainless steel.</p>
	<p>Hydraulic pump</p> <p>An air driven amplification pump is used to pressurize the oil. This pressurized oil is used to move the piston down or up. The oil pressure is proportional to the air supply pressure in static conditions (piston not moving).</p>
Reset button	Pneumatic push button to reset the hydraulic unit after the emergency button has been disengaged.
Emergency Stop	Pneumatic emergency stop to shut down the hydraulic pump in case of emergency.
"OR" function	Pneumatic function "OR" allowing emergency push button reset.
Air supply Valve	Pneumatic 2 way valve, used to supply the hydraulic pump with compressed air.
Motion Selector	Pneumatic switch to control the oil distributor in order to select the piston's motion (up, down, stop).
Pressure Regulator	Air pressure regulator to set the air pressure supply to the pneumatic amplification pump. The air pressure is linear with the oil pressure.
Oil distributor	Oil distributor controlled by the motion selector.
Filter	Breather filter for the oil reservoir.
Oil reservoir	Reservoir for the hydraulic oil with 15 L capacity.
Relief valve	Oil pressure relief valve to protect the column in case of an accidental over-pressure.
Pressure gauge	Pressure gauge indicating the oil pressure. This indication is used to determine the bed compression.
Packing valves	Manual 3-way ball valve to isolate the column from the pumping skid for the packing and unpacking operations.
Packing valve	Manual 3-way ball valve to select solvent direction toward the flange's or piston's side during packing operation in order to bleed the air and/or remove the slurry solvent.

The design of the Column is made in such a way to reduce as much dead volume as possible. All wetted parts of the column module are made of SS316L stainless steel, FEP and PTFE.

The **LC150.700.VE100** is rated to be operated in hazardous area.

EUROPE - Novasep Process
Phone: +33 (0)3 83 49 70 00
pharma-systems@novasep.com

NORTH AMERICA - Novasep Inc.
Phone: +1 610 494 0447
pharma-systems.norh-am@novasep.com

REST OF WORLD - Novasep Process
Phone: +33 (0)3 83 49 70 00
pharma-systems@novasep.com

ASIA COUNTRIES - Novasep Asia
Phone: +86 (0)21 3895 0252
pharma-systems.asia@novasep.com

INDIA - Novasep Partner
Nilsan Nishotech
Phone: +91 22 41515151
pharma-systems.india@novasep.com

JAPAN - Novasep Japan K.K
Phone: +81 03 3221 1960
japan@novasep.com