

Metal Detector AD-4971 Series

IP65
compliant

Capable of detecting metal contaminants in products, this system contributes to the delivery of safe products to customers.



- Protected from dust and water to IP65 standards. Hygienic design with the entire system washable.
- Suitable for use in HACCP program.
- Automatic sensitivity setting function.
- Easy operation with 7 inch color touch panel.
- Variable belt speed of 10-60m/min.
- Standard Ethernet I/O allowing easy networking via LAN.
- Inspection history function with the ability to record 100 inspection results in the internal memory. Capacity can be increased by using USB memory.
- Cleaning and maintenance is simple with a detachable conveyor belt.

Wheels are sold separately.

AND ...Clearly a Better Value
A&D Company, Limited
<http://www.aandd.jp>

7 inch color touch panel

The display utilises a high visibility touch panel color LCD with user friendly Graphic User Interface (audio guidance support function included).

Image import from USB

Product images can be quickly uploaded to the metal detector from USB memory, making product identification and upload fast and simple.



USB memory

Stores up to 1000 products

Products can be divided into 10 different groups, with up to 100 products able to be recorded within each group.

Modbus communication

Equipped with Modbus RTU/Modbus TCP as standard. With Modbus communication, seamless connection can be easily achieved.



Operations such as stopping and starting inspection, collecting data and changing product can all be set from an external device.



LCD screen



Touch panel PC



AD-4971 Metal Detector



AD-4961 Checkweigher

Ethernet

Display example

Normal display



Lissajous display



Bar graph display

Specifications

Model AD-4971 Series

Aperture size	Width	350mm		
	Height	100mm	170mm	250mm
	Pass height	80mm	150mm	230mm
Detection Sensitivity	Fe	φ0.3mm	φ0.5mm	φ0.7mm
	SUS	φ0.8mm	φ1.0mm	φ1.5mm
Dust / water resistance specifications	IP65 compliant			
Touch Panel	○			
2D graph display	○			
Menu with graphic display	○			
Audio guidance for operation	○			
Supports Modbus	○			
FTP server function	○			
History can be recorded in USB memory	○			
Accessibility to I/O box	○			
Maintenance	Gear drive system			
PLC interface(standard feature)	Modbus RTU/Modbus TCP, FTP server function(LAN), Relay output/Universal input			
External input	Non-voltage contact input 4 points			
External output	Relay output 8 points			

Modbus is a registered trademark of AEG Schneider Automation International

A&D

...Clearly a Better Value

A&D Company, Limited

3-23-14 Higashi-kebukuro, Toshima-ku, Tokyo 178-0013 JAPAN
Telephone:[81](3) 5391-6132 Fax:[81](3) 5391-6148
http://www.aandj.jp

A&D ENGINEERING, INC.

1756 Automation Parkway, San Jose, CA 95131 U.S.A.
Telephone:[1](408) 263-5333 Fax:[1](408) 263-0119

A&D Australasia Pty Ltd.

32 Dew Street, Thebarton, South Australia 5031 AUSTRALIA
Telephone:[61](8) 8301-8100 Fax:[61](8) 8552-7409

A&D INSTRUMENTS LTD.

Unit 24/26 Blacklands Way Abingdon Business Park,
Abingdon, Oxon OX14 1DY UNITED KINGDOM
Telephone:[44](1235) 550420 Fax:[44](1235) 550485

<German Sales Office>

Hamburger StraÙe 30 D-22826 Ahrensburg GERMANY
Telephone:[49](0) 4102 450230 Fax:[49](0) 4102 458231

A&D KOREA Limited

Manhattan Bldg. 8F, 36-2 Yoido-dong, Youngdeungpo-gu, Seoul, KOREA
Telephone:[82](2) 780-4101 Fax:[82](2) 782-4280

A&D RUS CO., LTD.

Vnroyskaya str.17, Moscow, 121367 RUSSIA
Telephone: [7] (495) 937-33-44 Fax: [7] (495) 937-55-66

A&D Instruments India Private Limited

509 Udyog Vihar Phase V
Gurgaon-122 016, Haryana, INDIA
Telephone:[91](124) 471-5555 Fax:[91](124) 471-5599