



6



maximum speed with minimal space

this compact centrifuge is ideal for protocols calling for fast spins with a higher RCF requirement  
 ideal for PCR®, microfilter cell separation, clinical & diagnostic applications, and HPLC protocols

- compact footprint and brush-less motor for quiet operation and low vibration
- select and set the digital speed display in RCF or RPM
- sample imbalance and tilt safety cut out
- safety interlock lid prevents opening while rotor is turning
- back lit display showing time, speed and operational information on the same screen
- quick-spin button for short spin requirements
- suitable for worldwide voltages 110 to 240V, supplied with 4 different plug sets
- uv-resistant plastic, increased useful life under harsh light conditions
- double insulated, low voltage power supply
- push button lid release
- manual override allows user to open lid in case of power failure

part no.	description
HS10050	gusto®, 110–240 VAC, 50/60 Hz



specifications:

**speed:** 500–12,500 RPM  
**rcf:** 15–9, 800 Xg  
**power:** 110 to 240 VAC, 50/60 Hz with 4 interchangeable power cords  
**dimensions:** 203 x 171 x 114 mm  
**two-year warranty**



package includes:

- high-Speed Mini-Centrifuge
- 12 place 1.5/2.0 mL tube rotor
- 32 place 0.2 mL tube rotor (singles, or 4 x 8 Strip)
- 12 tube adapters 0.2 mL
- 12 tube adapters 0.5 mL
- Universal double insulated, power adapter 110–240V 50/60 Hz, with 4 interchangeable cord types

