

GOTECH "the best partner" to raise your competition

TCS-2000 伺服控制拉力試驗機

Servo control system
Universal testina Machine

本試驗機廣泛應用於橡膠、塑膠、制鞋、皮革、金屬、電纜、紙品包裝類、木材.....等行業之成品、半成品試片之拉伸、壓縮、彎曲、抗折、撕裂、剝離、剪力、粘力.....等測試。

Gotech series tensile strength testers are widely applied to determining elongation,compression, flexing,tear,peeling,shear force,adhesive force,etc.of finished or semifinished products such as rubber,plastic,footwear,leathers,metal,wire,paqer,timber,etc.

型號 Model	TCS-2000	
容量選擇 Capacity(optional)	100, 200, 500 N; 1,2, 5, 10, 20, 30 KN	
單位切換 Unit (Switchable)	kgf, gf, lbf, N, kN, MPa, Pa	
荷重分解度 Load Resolution	1/200,000	
荷重精度 Load Accuracy	±0.5%	
力量放大倍率 Load Range	無段 Rangeless (full scales at the same amplification)	
最大行程 (不含夾具) Stroke (exclude the grips)	1100 mm	
有效寬度 Effective Width	400 mm	
測試速度 Test Speed	0.0001~1000 mm/min	
速度精度 Speed Accuracy	±0.5%	
位移分解度 Stroke Resolution	0.00004 mm	
數據採樣頻率 Sample Rate	200 times/sec	
訊號傳輸方式 Communication Interface	USB	
顯示方式 Display Method	U62 專用軟體 Dedicated Software	
馬達 Motor	AC 伺服馬達 servo motor	
體積 Dimension (WxDxH)	主機 Main Unit (高度不含水平腳 Height exclusive of footpad)	114×46×201 cm
	電腦及桌 Computer/ Desk	100 X 60 X 118 cm
重量 Weight (approx.)	主機 Main Unit	380 kg
	電腦及桌 Computer/ Desk	60 kg
電源 Power	1 φ , 220V, 50/60Hz, 15A 或指定 or specified by user	

- 各式夾具及伸長量測裝置.....等附件，依客戶需求（合約書）選配，本公司業務部也會給客戶最恰當之建議。
- The accessories such as the different grips, elongation measuring-devices... etc. are equipped according to the requirements specified in the contract; our sales representative will also give the proper suggestions to our customer beforehand.



了解更多產品信息，請登錄我司網站 www.gotech.biz