

AUTOMATED PENSKY-MERTENS CLOSED CUP FLASH POINT TESTER

apm-8



All New

Available in Oct, 2011

- SIMPLE & EASY OPERATION
- COMPACT DESIGN & ENERGY EFFICIENT
- CONFORMS TO STANDARD TEST METHOD

(ISO 2719, ASTM D93, IP34)

Model apm-8 is the automated Pensky-Martens Closed Cup flash point tester from Tanaka. When this eighth generation model was designed after 45 years of delivering the automated flash point testers to the petroleum industry, ease of operation and maintenance was sought.

A color display, minimum membrane switches and USB keyboard (option) allow for user friendly interface.

45 years know-how is condensed to this robust, newly accomplished designed body.

SINGLE ACTION SETTING

The cup cover and the stirrer are permanently mounted on a swing-arm assembly, which allows an easy handling of the test cup cover. It makes free from handling the hot cup cover after completing a test. The swing arm assembly can be lifted up to vertical position for easier test cup cleaning.

EASY OPERATION

Select a test mode and enter the expected flash point; while the instrument executes the test, you are free to do other lab work. The instrument follows the exact procedures prescribed in the test method, and the completion of the test cycle is signaled by beeps. The test result is brightly shown on the color LCD module.

INTERCHANGEABLE IGNITION SOURCE

apm-8 is equipped with both gas and electric igniter as the ignition source. It only takes a few minutes to switch from gas to electric or vice versa.

DRAFT PROTECTION SHIELD COVER

A tinted acrylic cover not only insures the flame integrity but reduces the glare from the electric igniter coil.

DATA HANDLING

The unit is equipped to store up to 200 test results and export to an optional printer or to a LIMS through an RS-232 port.

USB PORT

A USB port allows connecting USB keyboard for easy entering sample name and connecting USB flash memory for data copy to a PC or test conditions/parameters copy to the tester.

PASSWORD PROTECTION

With setting up password by the administrator, the device is protected against inadvertent change of parameters by the operator.

ALL-IN ONE DESIGN IN LIGHTWEIGHT

The all-in-one design is much lighter than old model, APM-7 by approximately 30%, which is world's smallest class in volume.

SPECIFICATIONS

TYPE	All –in one, microprocessor controlled
TEST STANDARDS	ISO 2719, ASTM D93, IP34
MEASURING RANGE	Ambient to 370°C
MEASUREMENT MODES	ASTM D93 A-normal, ASTM D93 A-special (search), ASTM D93 B-normal, ASTM D93 B-special, ASTM D93 C-normal, ASTM D93 C-special, and User custom
HEATER	Band type heater:530W @115V or 500W @230V
COOLING DEVICE	Forced air cooling by fan
DISPLAY	5.7 inch (117 x 88mm) color LCD with LED back light
STIRRING	100, 250 rpm (selectable)
TEMPERATURE SENSOR	PT-100 in stainless steel sheath
FLASH DETECTOR	CRC Thermocouple
IGNITION SOURCE	Gas ignition with automatic lighting or electric ignition. Interchangeable
BAROMETRIC CORRECTION	Automatic correction by built-in barometric pressure sensor
I/O PORT	RS-232C = 1 channel (for PC or Optional Printer) USB=1 channel (for USB keyboard or USB Flash Memory)
SAFETY SHUTDOWN	Automatically shuts off and the problem is reported by buzzer and display, in case: (a) EFP+20 °C or 370 °C is reached, (b) temperature sensor is found defective, (c) flash detector is found defective, (d) thermofuse is blown, (e) electric Igniter is blown, (f) built-in battery is found drained out, (g) test cover is not set in place, (h)control computer runs away (no display) (i) Stirring motor stopped
GAS SUPPLY (When Gas Ignition is used)	LP gas or natural gas (Max. pressure:10kPa)
POWER SUPPLY	100/120VAC or 220/240 VAC, 50/60Hz
POWER CONSUMPTION	720W MAX.
ELECTRICITY CONSUMPTION	170Wh for 1 test (about 60 min), 60gCO ₂ (@ 0.378kgCO ₂ /1kWh)
AMBIENT TEMP. RANGE	10°C to 35°C
DIMENSIONS & WEIGHT	230mm (W) × 470mm (D) × 390mm (H) 17kg

APPARATUS

CODE	PART NAME	REMARKS
APM-00-015	apm-8	Pensky-Martens Closed Cup Flash Point Tester

STANDARD ACCESSORIES

CODE	PART NAME	Qty	REMARKS
APM-02-001	Test Cup	1	
320-00-035	Thermofuse	1	Pack of 5, with Insulation Tube.
210-02-161	Gas Hose $\phi 9$ x $\phi 16$	1.5	Unit: m
170-01-041	Gas Hose Band	2	
APM-04-431	Windscreen for apm-8	1	
———	apm-8 MANUALS	1	Manuals for apm-8.

OPTIONAL ACCESSORIES

CODE	PART NAME	REMARKS
070-00-068	Printer, BS2-80TS	Prints out test data and instrument settings.
070-00-281	Mini USB Keyboard	Sample ID entering

SUGGESTED SPARES for 2 YEARS

CODE	PART NAME	Qty	REMARKS
APM-02-001	Test Cup	1	Refer to Standard Accessories.
320-00-035	Thermofuse	1	Pack of 5, with Insulation Tube.
ABL-01-003	Electric Igniter, EI-8	2	
APM-04-031	Temperature Sensor	1	
APM-03-032	Flash Detector	1	

We reserve the right of changes without prior notice.

Printed in Japan 1106(E)

 TANAKA SCIENTIFIC
上海旭风科学仪器有限公司 上海市闸北区万荣路388弄17号904室 200072 TEL: 021-66581985 FAX: 021-66581986 URL: http://www.shxf17.com Email: zhou-feng1027@163.com