


EUV/XUV Wavefront Sensor



Features





- ▶ Hartmann wavefront sensor for coherent and incoherent radiation
- ▶ Compact and self-supporting
- ▶ Achromatic
- ▶ Actinic characterization of:
 - EUVL plasma sources
 - Free Electron Lasers
 - HHG beams
- ▶ Real-time optics adjustment
- ▶ Single-pulse repeatability $\lambda/116$ (wrms) for EUV ($\lambda = 13.5$ nm)



Specifications

- | | |
|-------------------------|---|
| ▶ Wavelength range | < 1 nm ... 60 nm
(quantum converter) |
| ▶ Field of view | 9.0mm x 6.7 mm
(larger on request) |
| ▶ Dynamic range | 14 bit |
| ▶ Hartmann plate | precision pinholes
$\varnothing 75\mu\text{m}$, 250 μm pitch |
| ▶ Tilt range | $\pm 10^\circ$ |
| ▶ x/y translation range | $\pm 10\text{mm}$ |
| ▶ UHV compatible | mounted on CF63 flange |

- ▶ Hartmann plate (pinhole array)



▲ Spot pattern @ $\lambda=1.5$ nm
(LCLS / Stanford)

▲ Reconstructed
intensity profile

Wavefront measurement of Free Electron Laser FLASH (DESY/Hamburg) at $\lambda=13.5\text{nm}$, before (above) and after (below) adjustment of beam line optics (B. Flöter, K. Mann, K. Tiedtke et al. NIM A **635**, S108–S112 (2011))



Laser-Laboratorium
Göttingen e.V.

Laser-Laboratorium Göttingen e.V.
Hans-Adolf-Krebs-Weg 1
D-37077 Göttingen
www.llg-ev.de

Dr. Klaus Mann
kmann@llg-ev.de
Tel: +49-(0)551-5035-41
Fax: +49-(0)551-5035-99