CONSUMABLES

PHENOLIC RESIN					
REF.	DESIGNATION	COLOUR	USE	CHARACTERISTICS	
03001	Pack 2.5kg				
03101	Pack 10kg	Black			
03150	25kg				
03002	Pack 2.5kg			Shrinkage: low Hardness: 90 shore D	
03102	Pack 10kg	Green			
03151	25kg		Standard mounting media for soft to medium hard materials		
03003	Pack 2.5kg				
03103	Pack 10kg	Red			
03152	25kg				
03011	Pack 2.5kg	White			
03105	Pack 10kg	VVIIILE			
03010	Pack 2.5kg	Black fiber	Standard mounting media for soft	Shrinkage: low	
03111	Pack 10kg	glass	to medium hard materials	Hardness: 95 shore D	
03012	Pack 2.5kg	Conductive Phenolic (black carbon)	SEM applications or electrolytic polishing	Shrinkage: low Hardness: 90 shore D Conductivity: good	

ALLYLIC RESIN

REF.	DESIGNATION	COLOUR	USE	CHARACTERISTICS
030	05 Pack 2.5kg	Blue	Observation of sample edges	Shrinkage: very low
031	06 Pack 10kg			Hardness: 93 shore D

ACRYLIC RESIN

REF.	DESIGNATION	COLOUR	USE	CHARACTERISTICS	
03006	Pack 2.5kg	Copper	Powder. For electro-polishing or electrolytic etching	Shrinkage: low Hardness: 90 shore D Conductivity: good	
03007	Pack 2.5kg	Transparent	Powder. When a transparent mount	Shrinkage: low	
03108	Pack 10kg	Transparent	is required	Hardness: 88 shore D	

EPOXY

REF.	DESIGNATION	COLOUR	USE	CHARACTERISTICS	
03009	Pack 2.5kg				
03109	Pack 10kg			Shrinkage: very low Hardness:96 shore D	
03156	25kg				

MOUNT RELEASE AGENT

REF.	DESIGNATION	COLOUR	USE
03008	Mount release agent Silicone aerosol 500ml		Eases the remove of your mounted samples. Just spray into the mould of the mounting machine!

PRESI IS ALSO ...

CUTTING





Mecatome T330

CUTTING



POLISHING



HARDNESS TESTING




POLISHING













Automatic hot mounting machine, Mecapress 3, is a user-friendly machine, very easy to manipulate.





FUNCTIONALITIES

O REF. 53500

Width				
	W	ld	th	

320mm
Depth 560mm
Height closed lid 530mm
Height opened lid 620mm

Weight

65 kg

Conformity EC

MECAPRESS 3, new generation mounting press


MECAPRESS 3 is a fully automated hot mounting press. Very easy to use, MECAPRESS 3 offers all the features expected in a high precision machine: memorisation and adjustment of all mounting parameters, custom programmability, rapid cycle option and water saving mode. A powerful and flexible machine.







- New colour touch screen.
- Intuitive use.
- New heating and cooling technologies for fast cycles.
- New ergonomic design.





PRESI offers you also a whole range of hot mounting resins in order to meet all your needs!

CHARACTERISTICS

Automatic cycle
Fast cycle
Temperature adjustable
Heating time adjustable
Cooling time adjustable
Cooling mode adjustable
Pressure adjustable
Mould diameter
Intermediate ram (to allow two molds be made at the same time)
Easy interchangeable moulds
Possibility to stop the piston at the required position
Fast arm lock
Secure mould closing
Sensor for detecting if mould is closed
Mounting parameters adjustable
Mounting parameters readable on tactile screen
Memorised mounting processes
Cooling by pulse
Connectors to plug and control tank and re-circulating pump
Easy cleaning
Easy use and maintenance
Power
Electrical input
Air pressure (input)
Air connector diameter (input and output)
Water connector diameter (input and output)

ACCESSORIES

Mould sets

53505 Mould set Ø 25.4mm
53506 Mould set Ø 30mm
53507 Mould set Ø 31.7mm
53508 Mould set Ø 38.1mm
53509 Mould set Ø 40mm
53510 Mould set Ø 50mm

nte	rm	edi	iat	e	ra	m	s

Intermediate rams enable to 2 simultaneous mounts with
53416 Intermediate rams Ø 25.4mm
53420 Intermediate rams Ø 30mm
53421 Intermediate rams Ø 31.7mm
53422 Intermediate rams Ø 38.1mm
53423 Intermediate rams Ø 40mm
53424 Intermediate rams Ø 50mm





REF. 53416 / 53420 À 53424 REF. 53505 TO 53510

REF. 53515

✓
✓
From 100 to 200 °C, by step of 1 °C
From 0 to 9999 seconds, by step of 1 second
From 0 to 9999 seconds, by step of 1 second
✓
From 300 to 1.800 daN, by step of 1 daN (for a 6 bars compressed air network)
25.4/30/31.7/38.1/40/50mm
✓
✓
✓
✓
✓
v
✓
 ✓
More than 100 processes
✓
✓
✓
✓
> 2 KW
220 V Monophase 50/60 Hz / 8A
6-10 bars
Ø 10mm
Ø 12mm

able to achieve ts with only one mould.

25.4mm

31.7mm

38.1mm



Other accessories

53515 55 I recirculating tank and pump system. This recirculating tank and pump system. This recirculating system provides for closed circuit cooling of MECAPRESS 3 with the benefit of greatly reduced water use and the elimination of calcium carbonate build up from hard water supplies. It also allows the MECAPRESS 3 to be used in crease of the lab where there used in areas of the lab where there Environmentally friendly! • No more calcium problem Water saving

67750

Air compressor (for labs with no compressed air supply).