









Specifications		Connector	Dimensions																																																																																													
Sensor	ICX 285	<p style="text-align: center;">DC-In / Trigger</p>  <p style="text-align: center;">Hirose HR10A-10P-12S</p> <table border="1"> <thead> <tr> <th>Pin</th> <th>Signal</th> <th>Function</th> </tr> </thead> <tbody> <tr><td>1</td><td>GND</td><td>GROUND</td></tr> <tr><td>2</td><td>Vin</td><td>+15-24V</td></tr> <tr><td>3</td><td>DNC</td><td>Do not connect</td></tr> <tr><td>4</td><td>DNC</td><td>Do not connect</td></tr> <tr><td>5</td><td>DNC</td><td>Do not connect</td></tr> <tr><td>6</td><td>DNC</td><td>Do not connect</td></tr> <tr><td>7</td><td>Trigger in</td><td>Input trigger</td></tr> <tr><td>8</td><td>Trigger out</td><td>Output trigger</td></tr> <tr><td>9</td><td>DNC</td><td>Do not connect</td></tr> <tr><td>10</td><td>DNC</td><td>Do not connect</td></tr> <tr><td>11</td><td>DNC</td><td>Do not connect</td></tr> <tr><td>12</td><td>DNC</td><td>Do not connect</td></tr> </tbody> </table> <p style="text-align: center;">Camera Link Interface 26 pin MDR connector 3M 10226-1A10JL</p>  <table border="1"> <thead> <tr> <th>Pin</th> <th>Signal</th> <th>Function</th> </tr> </thead> <tbody> <tr><td>1</td><td>14</td><td>GND</td></tr> <tr><td>2</td><td>15</td><td>X0-/X0+</td><td>CL Data</td></tr> <tr><td>3</td><td>16</td><td>X1-/X1+</td><td>CL Data</td></tr> <tr><td>4</td><td>17</td><td>X2-/X2+</td><td>CL Data</td></tr> <tr><td>5</td><td>18</td><td>Xclk-/Xclk+</td><td>CL Clk</td></tr> <tr><td>6</td><td>19</td><td>X3-/X3+</td><td>CL Data</td></tr> <tr><td>7</td><td>20</td><td>Ser TC+/Ser TC-</td><td>Serial in</td></tr> <tr><td>8</td><td>21</td><td>Ser TFG-/Ser TFG+</td><td>Serial out</td></tr> <tr><td>9</td><td>22</td><td>CC1-/CC1+</td><td></td></tr> <tr><td>10</td><td>23</td><td>CC2-/CC2-</td><td>Not Used</td></tr> <tr><td>11</td><td>24</td><td>CC3-/CC3+</td><td>Not Used</td></tr> <tr><td>12</td><td>25</td><td>CC4+/CC4-</td><td>Not Used</td></tr> <tr><td>13</td><td>26</td><td>GND</td><td></td></tr> </tbody> </table>	Pin	Signal	Function	1	GND	GROUND	2	Vin	+15-24V	3	DNC	Do not connect	4	DNC	Do not connect	5	DNC	Do not connect	6	DNC	Do not connect	7	Trigger in	Input trigger	8	Trigger out	Output trigger	9	DNC	Do not connect	10	DNC	Do not connect	11	DNC	Do not connect	12	DNC	Do not connect	Pin	Signal	Function	1	14	GND	2	15	X0-/X0+	CL Data	3	16	X1-/X1+	CL Data	4	17	X2-/X2+	CL Data	5	18	Xclk-/Xclk+	CL Clk	6	19	X3-/X3+	CL Data	7	20	Ser TC+/Ser TC-	Serial in	8	21	Ser TFG-/Ser TFG+	Serial out	9	22	CC1-/CC1+		10	23	CC2-/CC2-	Not Used	11	24	CC3-/CC3+	Not Used	12	25	CC4+/CC4-	Not Used	13	26	GND		  
Pin	Signal		Function																																																																																													
1	GND		GROUND																																																																																													
2	Vin		+15-24V																																																																																													
3	DNC		Do not connect																																																																																													
4	DNC		Do not connect																																																																																													
5	DNC		Do not connect																																																																																													
6	DNC		Do not connect																																																																																													
7	Trigger in		Input trigger																																																																																													
8	Trigger out		Output trigger																																																																																													
9	DNC		Do not connect																																																																																													
10	DNC		Do not connect																																																																																													
11	DNC		Do not connect																																																																																													
12	DNC		Do not connect																																																																																													
Pin	Signal		Function																																																																																													
1	14		GND																																																																																													
2	15		X0-/X0+	CL Data																																																																																												
3	16	X1-/X1+	CL Data																																																																																													
4	17	X2-/X2+	CL Data																																																																																													
5	18	Xclk-/Xclk+	CL Clk																																																																																													
6	19	X3-/X3+	CL Data																																																																																													
7	20	Ser TC+/Ser TC-	Serial in																																																																																													
8	21	Ser TFG-/Ser TFG+	Serial out																																																																																													
9	22	CC1-/CC1+																																																																																														
10	23	CC2-/CC2-	Not Used																																																																																													
11	24	CC3-/CC3+	Not Used																																																																																													
12	25	CC4+/CC4-	Not Used																																																																																													
13	26	GND																																																																																														
Active area	2/3" sensor 10.2 mm(H) x8.3 mm (V)																																																																																															
Pixel size	6.45µm																																																																																															
Pixel clock	20 MHz																																																																																															
Active pixels	1360 x 1024																																																																																															
Frame rate	15 Fps full resolution																																																																																															
Channels	Channel 1 CIE-X Channel 2: CIE-Y Channel 3: CIE-Z																																																																																															
Alignment accuracy	Mechanically better than 1/4 th of a pixel																																																																																															
Dynamic range	>56 dB																																																																																															
Bit depths	8 bit 3 channel, 12 bit 3 channel																																																																																															
Gain	0 to 36 dB analog gain																																																																																															
Video output	Camera Link Base / GigE Vision																																																																																															
Trigger modes	Internal and external source (on CameraLink and Hirose connectors)																																																																																															
Synchronization	All Sensors clock synchronized. Smart trigger unit for advanced trigger schemes																																																																																															
Electronic shutter	Synchronized exposure with channel independent duration. (1 µs to 1s)																																																																																															
Control interface	All commands through Camera Link serial interface																																																																																															
Lookup tables	Lookup tables available in 8bit mode, full access to table entries. Table data programmed in flash memory (on request)																																																																																															
External control capability *)Selectable per channel	Gain*, exposure*, lookup tables*, region of interest, image bit depth, trigger source																																																																																															
Weight	785 grams excluding lens																																																																																															
Dimensions	100 x 78 X 124 mm																																																																																															
Lens mount options	F-mount or M42 custom lens																																																																																															
Operating temperature	-20 - +50 °C																																																																																															
Regulations	CE (EN 61000-6-2 EN 61000-6-3), FCC Part 15 class B, RoHS/WEE																																																																																															
Back focal length	≥ 46.50 mm in air																																																																																															
Power	18-24V DC +/--10%, 9W																																																																																															
Humidity	20-90% Non condensing																																																																																															



Examples

Shown is the actual camera response curve closing matching CIE.

The filters are not compensated for sensor responsivity

Camera needs to be calibrated by customer and is dependent on the lens used