

Immersion Thermostat with KISS-Controller. Powerful pressure and suction pump made of industrial plastic material. Moistened parts in stainless steel or plastics. With adjustable overtemperature protection according to DIN 12876.

NEW: KISS controller:

KISS combines state-of-the-art technology with simple operation and stylish design. Models with KISS controller are suitable for routine tasks in research and industry and are convincing as practice oriented basic equipment:

- \* Large, bright OLED display
- \* Simple operation with menu navigation
- \* Simultaneous display of set point, internal temperature, Tmin and Tmax
- \* Status displays for pump, cooling and heating
- \* USB (Device) and RS232 interfaces
- \* Overtemperature protection, Safety class 3 (FL)
- \* Autostart function for power failure
- \* 3 colour versions available: grey (standard), blue, red

Option: Pt100 sensor connection #10519 to display (not control) e.g. of the process temperature (only available factory fitted, additional charge).

3-2-2 warranty - registration required.

## Technical data according to DIN 12876

Operating temperature range	25...200 °C
with water cooling	20...200 °C
with refrigerator	-30...200 °C
Temperature stability at 70°C	0,05 K
temperature set point / display	digital
Internal temperature sensor	Pt100
Alarm message	optic, acoustic
Safety classification	Class III / FL
Heating power	2 kW
max. delivery	14 l/min
max. delivery pressure	0,25 bar
max. delivery (suction)	10,5 l/min
max. delivery pressure (suction)	0,17 bar
Immersion depth	150 mm
Overall dimensions WxDxH **	132x163x312 mm
Net weight	4 kg
Power supply requirement	230V 1~ 50/60Hz
Power input	2,1 kW
max. current	10 A
min. Fuse (1 phase)	10A
max. Fuse (1 phase)	16A
Degree of Protection	IP20
min. ambient temperature	5 °C
max. ambient temperature	40 °C



Order-No.: 2035.0012.98

from Serial-No.: **249541** 1.0/17

Technical details and dimensions are subject to change. No liability is accepted for errors or omissions. Illustrations can deviate from the original.

Included Accessories:  
screw clamp #30541.

Optional accessories:

pump adaptor #19606, hose connector NW8/NW12, nozzle #33288, cooling coil #30554, temperature control / - connection hoses, thermofluids, tempering container made of polycarbonate or stainless steel, further accessories, etc.: see catalog.

## Technical data according to DIN 12876

---

Output data valid for: Room temperature 20° C

In accordance with EN60034-1 the following voltage and frequency tolerances are valid:

Voltage + / - 10%, as long as the frequency tolerance does not run in the opposite direction.

Example: -10% voltage and + 3% frequency -> not allowed !

-10% voltage and -3% frequency -> allowed.

Information to Electromagnetic compatibility:

Classification (disturbance) to EN55011: Class A, Group 1

Special Case: Acetone and Polyglycol: The plastic pump is not resistant against acetone and polyglycols (depending on the manufacturer). It is recommended that water is mixed with either glysantine or ethylene glycol for freeze protection. A more resistant plastic is available on request at an additional cost.

\*\* Please respect space requirements. See operating conditions at [www.huber-online.com](http://www.huber-online.com)