

Zero Air A2, A5, A10, A30

Laboratory Zero Air Gas Generator



中国授权代理商：海蓝嘉胜科技(北京)有限公司
电话:010-84786125 邮箱: sales@highlandbest.com

MODEL	A2	A5	A10	A30
Technologies Employed	Catalyzer			
Flow Rate ¹	2 SLPM	5 SLPM	10 SLPM	30 SLPM
Output Pressure	0 to 7 barg / 0 to 100 psig			
Total Hydrocarbon Residual (as methane)	< 0.05 ppm			
Input Air Requirements	Particulate < 0.1 mg/m ³ (≤ 0.01 μm) Oil vapors ≤ 0.01 mg/m ³ Moisture ≤ 3°C (37°F) dew point in pressure 0 to 7.6 barg (0 to 110 psig)			
Air Compressor	No			
Electrical Supply ²	120 VAC ± 10%, 50/60 Hz 230 VAC ± 10%, 50/60 Hz			
Ambient Operating Temperature	60°F to 100°F / 16°C to 38°C			
Ambient Humidity	≤ 80% RH, non-condensing			
Max Altitude	2000 m / 6560 ft above sea level			
Unit Dimensions (H x W x D)	15.5" x 12" x 8" 39.4 cm x 30.5 cm x 20.3 cm			
Unit Weight	24 lbs / 10.9 kg			27.5 lbs / 12.5 kg
ADDITIONAL FEATURES				
	Wall-mountable			
COMPLIANCE				
	CE, IEC/UL/CSA 61010-1			

Specifications are subject to change.


¹ Measured at standard conditions: 21°C, 1 Atmosphere

² Electrical supply voltage is factory configured.

* Organic compounds in the ambient or input air will negatively affect performance.



中国授权代理商：海蓝嘉胜科技(北京)有限公司
 电话:010-84786125 邮箱: sales@highlandbest.com



MADE IN USA