

# Falcon III EMCCD - NEW

Digital Monochrome Scientific Frame Transfer EMCCD

1024 x 1024 • 10µm x 10µm pixels • Cooled to -100°C • 1MP Scientific •



## Key Features and Benefits

*NEXT GENERATION* photon counting sensitivity

- **Lower read noise of <0.01e-**  
Best sensitivity of any camera technology
- **Faster readout in full resolution**  
x 3 times faster than previous generations
- **Higher EM gain of x 5000**  
See single photon events
- **Up to 95% QE from back-illuminated sensor**  
Optimum Photon collection
- **Strong UV and NIR reponse and ultrawide bandwidth**  
From 200nm through to 1100nm
- **Deep cooled to -100°C**  
For minimal background events

**EMCCD - GEN III**  
**A NEW GENERATION**

*The Photon Harvester!*

Resolution	<b>1024 x 1024</b>
Pixel Size	<b>10µm x 10µm</b>
Readout Noise	<b>&lt;0.01e-</b>
Frame Rate	<b>34fps</b>
Cameralink	<b>16bit</b>

## Specification for Falcon III EMCCD

Sensor Type	1" Back Thinned Frame Transfer EMCCD
Active Pixel	1024 x 1024
Pixel Size	10µm x 10µm
Active Area	10.2mm x 10.2mm
Full Well Capacity	35,000 electrons
Shift Register Well Depth	200,000 electrons
Non-Linearity	<1%
Readout Noise	<0.01 electrons with EM gain ON, <60 electrons with EM gain OFF
Full Resolution Frame Rate	34fps
Exposure Time	1ms to >1hr
Dark Current (@ -100°C)	0.0002 e/p/s
Digital Output Format	16 bit CameraLink (base configuration)
Peak Quantum Efficiency	95%
Spectral Response	200 - 1100nm
Cooling	-100°C with +10°C coolant
Binning	1x1 up to 32x32
Lens Mount	C-Mount
Synchronisation	Trigger IN and OUT - TTL compatible
Power Supply	12V DC ±10%
Total power consumption	<100W
Operating case temperature	-20°C to +55°C
Storage Temperature	-30°C to +85°C
Dimensions	129mm x 112mm x 94mm
Weight (no lens)	<1.5Kg

Raptor Photonics Limited reserves the right to change this document at any time without notice and disclaims liability for editorial, pictorial or typographical errors.

## Ordering Information

### Camera

Falcon EM351 digital B/W camera	RPL-FA351V-BV-CL
Falcon Power Supply Cable	RPL-KY-CBL

### Optional Accessories

EPIX(R) EB1 base CL card	RPL-EPIX-EB1
EPIX(R) base Notebook CL card	RPL-EPIX-ECB1-34
EPIX(R) base Notebook CL card	RPL-EPIX-ECB1-54
EPIX(R) XCAP STD software	RPL-XCAP-STD
CameraLink Cable, 2m <sup>2</sup>	RPL-CL-CBL-2M
Optical Visible lenses <sup>3</sup>	RPL-xx-xxxx

Note 1: Extended operating temperature range on request.


Note 2: Longer CL cable available up to 25M

Note 3: Please consult us to check our range of lenses

Demo is available on request.  
Pricing AOR subject to volumes.

Detailed technical drawings  
can be downloaded at  
[www.raptorphotonics.com](http://www.raptorphotonics.com)

## Quantum Efficiency



## Applications

- Adaptive Optics and Astronomy
- Calcium signaling
- Fluorescence imaging / spectroscopy
- Flow cytometry
- FRET / FRAP / TIRF
- Genome sequencing
- High content screening
- High resolution fluorescence imaging
- Hyperspectral imaging
- Live cell imaging
- Photon counting
- Single molecule detection
- Solar cell inspection
- X-ray & High energy

Document #: USFA351V-BV-CL 1217R1