TECHNICAL FEATURES

| Manual polishing machines MINITECH | | | | | | | | |
|--|---------------|---------------|---------------|---------------|---------------|---------------|--|--|
| Polishing machine model | 250 SP1 | 250 DP1 | 250 DP2 | 300 SP1 | 300 DP1 | 300 DP2 | | |
| Number of platens | 1 | 2 | 2 | 1 | 2 | 2 | | |
| Number of motors | 1 | 1 | 2 | 1 | 1 | 2 | | |
| Diameter of the polishing platen | 200 to 250 mm | 200 to 250 mm | 200 to 250 mm | 250 to 300 mm | 250 to 300 mm | 250 to 300 mm | | |
| Rotation speed (in increment of 1RPM) | 20 to 700 RPM | | |
| Rotation direction : clockwise & counter-clockwise | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | | |
| Timer | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | | |
| Speed display | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | | |
| Time display in seconds | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | | |
| Display of applied force | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | | |
| Memorizing settings | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | | |
| Watering by multijet ramp | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | | |
| Motor power | 750 W | 750 W | 2 x 750 W | 1500 W | 1500 W | 2 x 1500 W | | |
| 700 RPM spin function | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | | |
| High engine torque | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | | |
| Constant speed of the platen | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | | |
| Immediate stop of the platen | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | | |
| Bearing transmission | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | | |
| Over-bowl | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | | |
| Progressive acceleration of the platen | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | | |
| Splash guard | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | | |
| Power supply* | 230 VAC | | |
| Frequency | 50 - 60 Hz | | |
| Max. current | 8 A | 8 A | 8 A | 8 A | 8 A | 8 A | | |
| Water outlet | Ø 12 mm | | |
| Water evacuation | Ø 32 mm | | |

^{*} possibility 110 VAC : 50 - 60 Hz

| MINITECH accessories | | | | | |
|---|----------------------|----------------------------------|--------------------------------|--|--|
| Drive platen with aluminium positioners | Almagtech platen | Circular paper holder (metal) | Circular paper holder (PVC) | | |
| | | | | | |
| ø 196 mm. Ref. 56350 | ø 200 mm. Ref. 67822 | ø 200 mm. Ref. 56054 | ø 200 mm. Ref. 56067 | | |
| ø 245 mm. Ref. 67221 | ø 250 mm. Ref. 67820 | ø 250 mm. Ref. 56055 | ø 250 mm. Ref. 56058 | | |
| | ø 300 mm. Ref. 67821 | | ø 300 mm. Ref. 56069 | | |

| PVC platen with cone housing | Full PVC platen with machined cone | PVC lid |
|------------------------------|------------------------------------|----------------------|
| | | P |
| ø 230 mm. Ref. 56066 | ø 200 mm. Ref. 56053 | ø 250 mm. Ref. 66050 |
| ø 250 mm. Ref. 56062 | ø 250 mm. Ref. 56063 | ø 300 mm. Ref. 66025 |
| ø 300 mm. Ref. 57163 | ø 300 mm. Ref. 56064 | |













MINITECH

250 SP1 | 250 DP1 | 250 DP2 300 SP1 | 300 DP1 | 300 DP2









MINITECH, the latest generation of manual polishing machines BY PRESI

FREQUENCY INVERTER

« Inverter » technology which controls the three-phase motor:

- Gives exceptional power to the platen
- Ultra-precise speed variation
- Constant torque and speed whatever the applied load
- Progressive acceleration and immediate stop
- 2 directions of rotation
- Thermal security in case of prolonged overload

Equipped with platens from Ø200 to 300 mm, the new range of MINITECH manual polishing machines has the most advanced technologies.

Unrivaled motor power.

Thanks to a motor power from 750W to 1500W, the entire PRESI experience is condensed in this most complete range on the market.

User-friendly, reliable and robust, MINITECH provides a simple answer to all needs.

Robustness and character.


With its affirmed style and edged lines, this new range is distinguished by its new design with an easily recognizable sleek and refined carbon look.

Accessories 100% compatible with the older generation of MINITECH

MINITECH range

Platen diameters: 200 to 250 mm

MINITECH 250 SP1



Width: 510 mm Depth: 810 mm Height: 330 mm Weight: 35 kg

Platen(s): 1 Motor(s): 1 Watering ramps(s): 1

 ϵ

MINITECH 250 DP1



Ref. 66410

Width: 920 mm Depth: 735 mm Height: 330 mm Weight: 50 kg Platen(s): 2 Motor(s): 1 Watering ramps(s): 2 Removable bowl(s): 2

 ϵ

MINITECH 250 DP2



Width: 920 mm Depth: 735 mm Height: 330 mm Weight: 58 kg Platen(s): 2 Motor(s): 2 Watering ramps(s): 2

 ϵ

Platen diameters: 250 to 300 mm

MINITECH 300 SP1



Width: 620 mm Depth: 875 mm Height: 330 mm Weight: 42 kg

Platen(s): 1 Motor(s): 1 Watering ramps(s): 1 Removable bowl(s): 1

 ϵ

MINITECH 300 DP1



Widht: 1100 mm Depth: 810 mm Height: 330 mm Weight: 60 kg

Platen(s): 2 Motor(s): 1 Watering ramps(s): 2 Removable bowl(s): 2

(€

MINITECH 300 DP2



Width: 1100 mm Depth: 810 mm Height: 330 mm Weight: 70 kg Nb plateau(x): 2 Motor(s): 2 Watering ramps(s): 2 Removable bowl(s): 2

 ϵ

A multi-jet ramp with flow control cools the platen evenly and reduces water consumption.

ENGINE POWER The machines are equipped with powerful motors controlled by frequency inverter.

The body and the composite tank exclude any oxidation.

Easy maintenance

Removable over-bowl easy to clean. The tank incorporates an

anti-splah device that prevents

any projection.



Large touchscreen

- 7"TFT LCD color display, 16/9
- Ergonomic and intuitive user interface
- Many features:
- Speed and direction of rotation
- Sprinkling
- Duration of the step (counting and countdown of time)

Practical

Convenient and quick access to the machine emergency stop button to immediately stop its operation.

Emergency stop button

- Memorization of 6 polishing programs
- A gauge displays in real time the pressure applied on the platen
- Parameters can be changed during the polishing cycle



