

PURA™

PURA 系列通用恒温水浴槽

推荐使用范围: 室温 +5 ~ +80.0℃

使用新的全平面加热系统及内槽超硬珉琅镀层技术

- 防水防尘操作面板, 高亮白光 LED 显示, 可以显示实际温度值和设定值

内槽超硬珉琅瓷镀层

- 玻璃般坚硬, 防刮伤, 只有暴力破坏才能损伤镀层
- 卫生级洁净, 细菌无法在镀层表面附着生长, 不产生菌膜
- 超级耐腐蚀, 所有与液体接触部分均耐腐蚀 (去离子水, 3% 盐水适用)
- 清洁超简单, 浴槽无死角, 无须清洁剂, 直接擦拭即可清洁

全平面加热系统

- 加热速度快, 最高的加热速率 / 体积比
- 温场极均匀, 专门设计的自然循环模式, 不使用循环泵即可保证极高均匀性
- 极限省空间, 浴槽容积与外部尺寸比最大
- 水深跨度宽, 最低 1-2cm 水深即可开始实验, 适合一些低矮器皿的恒温

全面的安全保障

- 设备具备防干烧功能
- 低液位声光报警功能和自动断电功能

使用及操作简便

- 标配集成式的放水阀, 接口及软管, 放水操作简单省力
- 试管架自沥水功能, 一提, 一插, 即可轻松实现试管沥水, 保证实验台及操作者的洁净
- 透明浴槽盖采用无工具安装设计, 并可耐受 100℃ 高温
- 可使用沙浴, 金属粒浴 (加热功率需要提前调整)
- 标配计时功能, 倒计时结束后报警通知, 可选继续运行或自动关机
- USB 通讯, 和电脑连接, 实现远程开关机, 设定温度, 读取温度, 加热功率等



多种规格可选: PURA 4/10/14/22/30 共 5 种规格, 最大 30L


技术信息

订货号	型号	推荐使用范围 ℃	分辨率 ℃	稳定性 ℃	加热功率 kW	槽开口尺寸 WxL/D cm	外部尺寸 WxL/Hcm	内充容积 L	重量 kg	可放置试管架 个
9550404	PURA 4	室温 +5~80.0	0.1	±0.2	0.8	12 x 27 / 17	21 x 38 x 30	0.4~4.8	5.05	1
9550410	PURA 10	室温 +5~80.0	0.1	±0.2	1.3	22 x 27 / 17	31 x 38 x 30	1~10	7.1	2
9550414	PURA 14	室温 +5~80.0	0.1	±0.2	1.3	30 x 27 / 17	42 x 38 x 30	1~14	9.2	3
9550422	PURA 22	室温 +5~80.0	0.1	±0.2	2	54 x 27 / 17	63 x 38 x 30	2~22	13.1	5
9550430	PURA 30	室温 +5~80.0	0.1	±0.2	2	76 x 27 / 17	85 x 38 x 30	2~30	17.2	7

PURA 系列附件

Lift-up bath covers transparent, up to +100 °C

订货号	描述	适用型号
9 970 280	Lift-up bath cover	适合 PURA 4
9 970 281	Lift-up bath cover	适合 PURA 10
9 970 282	Lift-up bath cover	适合 PURA 14
9 970 283	Lift-up bath cover	适合 PURA 22
9 970 284	Lift-up bath cover	适合 PURA 30



带孔不锈钢平槽盖 (含高品质塑料变径圈) 烧杯和三角瓶可以直接放置在固定圈中

订货号	描述	适用型号
9 970 270	Flat bath cover with 4 openings 92 mm Ø	适合 PURA 10
9 970 271	Flat bath cover with 1 opening 190 mm Ø	适合 PURA 10
9 970 272	Flat bath cover with 6 openings 92 mm Ø	适合 PURA 14
9 970 273	Flat bath cover with 8 openings 92 mm Ø	适合 PURA 22
9 970 274	Flat bath cover with 6 openings 115 mm Ø	适合 PURA 22
9 970 275	Flat bath cover with 2 openings 190 mm Ø	适合 PURA 22
9 970 276	Flat bath cover with 10 openings 115 mm Ø	适合 PURA 30
9 970 277	Flat bath cover with 3 openings 190 mm Ø	适合 PURA 30



Dentistry accessories

订货号	描述	适用型号
9 970 331	Stents lifter	适合 PURA 4
9 970 332	Stainless steel hygiene insert	适合 PURA 4



试管架 (+100°C, 聚丙烯材质)

订货号	描述	适用型号
9 970 300	Test tube rack for 60 tubes 100 x 16/17 mm dia.	适合 PURA
9 970 301	Test tube rack for 90 tubes 75 x 12/13 mm dia.	适合 PURA
9 970 303	Test tube rack for 21 tubes 30 mm dia.	适合 PURA



附加配件

订货号	描述	适用型号
8 970 010	防蒸发塑料球, 聚丙烯, 空心 20 mm 直径 (1000 个 / 包)	适合 PURA



Aqua-Stabil 浴槽保护液

可以防止藻类和菌类的生长, 颜色变化将指示保护液是否已经失效, 以便使用者及时添加新的保护液

订货号	描述	适用型号
8 940 006	6 瓶 /Pack. 100mL/ 瓶	适合 PURA
8 940 012	12 瓶 /Pack. 100mL/ 瓶	适合 PURA
9 940 200	Descaling Agent 1 Liter	适合 PURA



压瓶环

- 金属材料加 PVC 保护层; 非常适用于固定各种规格的三角瓶和锥形瓶;
- 可以将烧杯, 锥形瓶, 容量瓶等固定在内置提篮或器皿固定夹上, 用于清洗或脱气。

订货号	型号	颜色	尺寸 (OD) x (ID)	重量	材质
5660	S 型	红色	Ø 70 x Ø 27 mm	0.3 kg	铅 (PVC 涂层)
5661	M 型	黄色	Ø 105 x Ø 52 mm	0.5 kg	铅 (PVC 涂层)
5662	L 型	蓝色	Ø 140 x Ø 76 mm	1.2 kg	铅 (PVC 涂层)

