

## AF1103A



### Characteristics

<b>External Dimensions (W x D x H)</b>	cm 59,2 x 67,5 x 113
<b>Structure and Insulation</b>	stainless steel inside and outside
<b>Height adjustable Feet</b>	
<b>Kind of ice</b>	flakes
<b>Motor cooling</b>	air
<b>Production Kg/24h (up to)</b>	108
<b>Bin capacity (kg)</b>	30
<b>Weight</b>	kg 65

### Technical data

#### Details

- Refrigerant type: R404 CFC free
- Mains Voltage: 230V/1/50Hz
- Power Consumption: 12,5 kW/h
- Water consumption l/h: 3,3
- Electrical consumption: 470 W
- Fuse (A): 10
- Cooling Capacity Btuh/W: 3270
- Water temperature min/max: 5°C-35°C
- Pressure min/max: 1 bar/5 bar
- Noise level < 66 dB
- Ambient Temperature: +10/+32 °C; humidity 60%

**In accordance with** 2014/30/CE, 2014/35/CE and following modifications

**Package** Strong Cardboard on wooden pallet

## AF1124A



### Characteristics

<b>External Dimensions (W x D x H)</b>	cm 95 x 65,5 x 91,5
<b>Structure and Insulation</b>	stainless steel inside and outside
<b>Height adjustable Feet</b>	
<b>Kind of ice</b>	flakes
<b>Motor cooling</b>	air
<b>Production Kg/24h (up to)</b>	120
<b>Bin capacity (kg)</b>	40
<b>Weight</b>	kg 78

### Technical data

#### Details

- Refrigerant type: R404 CFC free
- Mains Voltage: 230V/1/50Hz
- Power Consumption: 14,4 kW/h
- Water consumption l/h: 3,8
- Electrical consumption: 600 W
- Fuse (A): 10
- Cooling Capacity Btuh/W: 4845
- Water temperature min/max: 5°C-35°C
- Pressure min/max: 1 bar/5 bar
- Noise level < 64 dB
- Ambient Temperature: +10/+32 °C; humidity 60%

**In accordance with** 2014/30/CE, 2014/35/CE and following modifications

**Package** Strong Cardboard on wooden pallet