



Lightweight, caseless fine dust aerosol spectrometer for integration in carrier systems, battery powered (Photo: Cased for flight drone)

## Benefits

- Flexible possibilities for installation and application due to small dimensions and very light weight
- Continuous and simultaneous real-time measurement of multiple PM values
- Additional information based on particle number concentration and particle size distribution
- Highly independent due to battery operation
- Up to six hours measuring time in battery mode
- Light source: LED
- PDAnalyze Fidas® software for individual analysis of your measurement data on an external PC
- Low maintenance
- External check of calibration on site possible
- Intuitive and easy to operate
- Reliable function

## Applications

- Integration in carrier systems such as, e. g., drones (for example Fidas® Fly 200) or unmanned vehicles
- Integration in one's own measurement setup, housing or payload unit



<https://www.palas.de/product/fidasfly100>

## Datasheet

Parameter	Description
<b>Interfaces</b>	Wi-Fi (optional USB)
<b>Measurement range (size)</b>	0.18 – 40 µm (2 measuring ranges)
<b>Size channels</b>	64 (32/decade)
<b>Measuring principle</b>	Optical light-scattering
<b>Measurement range (number C<sub>N</sub>)</b>	0 – 20,000 particles/cm <sup>3</sup>
<b>Volume flow</b>	1.4 l/min
<b>Dimensions</b>	9 • 15 • 24 cm (H • W • D)
<b>Weight</b>	ca. 1 kg (without battery and housing)
<b>Data logger storage</b>	32 GB
<b>Measurement range (mass)</b>	0 – 1,500 µg/m <sup>3</sup>
<b>Reported data</b>	PM1, PM2.5, PM4, PM10, TSP, Anzahlverteilungen

**Palas GmbH**  
 Partikel- und Lasermesstechnik  
 Greschbachstrasse 3 b  
**76229 Karlsruhe**  
 Germany

**Managing Partner:**  
 Dr.-Ing. Maximilian Weiß, Frank Mayer  
**Commercial Register:**  
 register court: Mannheim  
 company registration number: HRB 103813  
 USt-Id: DE143585902



**Contact:** E-Mail: [mail@palas.de](mailto:mail@palas.de) Internet: [www.palas.de](http://www.palas.de) Tel: +49 (0)721 96213-0 Fax: +49 (0)721 96213-33