

LABSTAC

**CO2 INCUBATOR
WATER JACKETED**



CO2 INCUBATOR WATER JACKETED

Water jacketed CO2 incubators are ideal for cell culture applications. These are designed to provide uniform temperatures and highly stable CO2 environments that are necessary to prevent shocks to cells. Precisely controlled, accurate, pure environment throughout the culturing process is maintained. High precise gas sensor is applied with automatic start function. These incubators are an ideal solution for labs involved with potential power disruption or significant ambient temperature fluctuations affecting the integrity of their cultures.

Used in Tissue Engineering, Vitro fertilization, Cell Culturing, Tissue culturing, Mammalian cell research, Oncology studies., Oncology studies.

Also known as Laboratory CO2 Incubator Water Jacketed.

IO21 WATER JACKETED CO2 INCUBATOR

High precise gas sensor is applied with automatic start function

HEPA filter, 0.3um, Efficiency:99.998%

RS232 interface

Internal glass door

Advanced fuzzy logistic PID control and menu operating interface

Full arc internal structure is treated with electrolytic polishing

Pressure compensation hole

Water reservoir volume: 3L

Alarms: Intelligent alarm, temperature deviation alarm and CO2 density deviation alarm functions etc.

Over temperature protection system



SPECIFICATIONS

Model	IO211	IO212
Capacity	185 L	
Temperature Range	RT +5~55°C	
Temperature Accuracy	±0.1°C	
Temperature Control Alarm	≥±0.1°C(adjustable)	-
CO2 Range	0-20%	
CO2 Accuracy	5%±0.1%	
CO2 Sensor	TCD	IR
CO2 Alarm	≥±0.1% (adjustable)	
CO2 Recovery Time	About 1%/min	
CO2 Filter Efficiency	99.998%	
Relative Humidity	95±3%	
Jacket Type	Water Jacketed	
Temperature Sensors	PT1000	
Internal Dimension (WxDxH)	540x505x680 mm	
Overall Dimension (WxDxH)	660x630x1105 mm	
Shelves/Trays	4	
Power Supply	220 V 50 Hz/60 Hz	

IO22 CO2 INCUBATOR WATER JACKETED

Microprocessor temperature and CO2 controller

Water reservoir volume: 3L

Alarms: Power interruption, High/Low temperature, CO2 deviation, low RH programmable alarm, Door ajar, Independent over heat protection

RS232 interface

Type 304 Stainless steel shelves



SPECIFICATIONS

Model	IO221	IO222
Capacity	185 L	
Water Jacket Volume	43.5 L	
Temperature Range	5°C above ambient temperature to 55°C	
Temperature Stability	±0.1°C	
Temperature Uniformity	±0.2°C	
CO2 Range	0-20%	
CO2 Stability	±0.1%	
CO2 Sensor	IR	TCD
CO2 Inlet Pressure	0.1 Mpa	
Filter	0.3 um, Efficiency:99.998% (for CO2)	
Relative Humidity	≥ 95%	
Jacket Type	Water Jacketed	
Inner Door	one inner door standard	
Interior	Type 304, mirror finish, stainless steel	
Exterior	Cold-rolled steel, powder coated	
Temperature Sensors	PT1000	
Internal Dimension (WxDxH)	544x504x681 mm	
Overall Dimension (WxDxH)	655x656x1030 mm	
Shelves/Trays	3 standard, 11 maximum	
Weight	110 kg	
Power	430 W	
Power Supply	220 V/50 Hz (standard), 110 V/60 Hz (Optional)	

ACCESSORIES

Accessory Code	Name	Units
IX1007	Standard shelf	3 Sets
IX1008	Electric siphon pump	1 Set
IX1032	Water tray	1 Set

OPTIONAL ACCESSORIES

Accessory Code	Name	Description	Dimension
IX1011	Small CO2 inlet filter		
IX1015	CO2 steel cylinder auto-switch device		
IX1016	CO2 regulator		
IX1017	4 in 1 CO2 steel cylinder auto-switch device		
IX1018	Air connector		
IX1033	Shelf	Including :shelfx1, shelf supportx2	
IX1034	Plastic filler		
IX1035	Stainless steel plate		1/2x2.5"
IX1036	HEPA filter		
IX1037	Floor stand for 1 incubator	High 600 mm with castor	
IX1038	Floor stand for 2 stacked incubators	High200 mm without castor	

LABSTAC

LABSTAC LTD

Kemp House 152 – 160 City Road, London, EC1V 2NX, United Kingdom
Email: contact@labstac.com | Website: www.labstac.com