

LABSTAC

PORTABLE AUTOCLAVE



PORTABLE AUTOCLAVE

Portable Autoclave is used for general purpose sterilization. Saturated steam is used to sterilize articles rapidly and efficiently. It is also used as a cooker in plateau areas and also for making high quality drinking water in Drinking Water Plant.

Used in Medical, Research Institutions, Laboratory, Drinking Water Plant, Food industry, Hospital, Agriculture, Scientific Research..

Also known as Portable Sterilizer, Steam Autoclave Sterilizer, Portable Autoclave, Pressure Steam Sterilizer, Portable Pressure Steam Sterilizer, Dental Autoclave.

AP11 PORTABLE AUTOCLAVE

Fully stainless steel structure.

Electric or LPG heated.

Double scale indication pressure gauge.

Easy to operate, safe and reliable.



SPECIFICATIONS

Model	AP111	AP112
Capacity	18 L	24 L
Function	Electric or LPG heated.	
Sterilization Temperature	126°C	
Working Pressure	0.14-0.16 Mpa	
Maximum Working Pressure	0.165 Mpa	
Chamber Dimension	280x260 mm	280x390mm
Overall Dimension (LxWxH)	410x410x430 mm	410x410x550 mm
Chamber Material	Stainless Steel	
Weight	14/16 kg	15/17 kg
Power	2 KW	
Power Supply	220 V, 50 Hz	

AP11 PORTABLE AUTOCLAVE

Fully stainless steel structure.
Double scale indication pressure gauge.
Electric heated.
Easy to operate,safe and reliable.
Water Tap.



SPECIFICATIONS

Model	AP113	AP114
Capacity	18 L	24 L
Function	Electric heated	
Sterilization Temperature	126°C	
Heat Average	≤1°C	
Working Pressure	0.14-0.16Mpa	
Maximum Working Pressure	0.165 Mpa	
Chamber Dimension	280x260 mm	280x390mm
Overall Dimension (LxWxH)	410×410×520 mm	410×410×630 mm
Chamber Material	Stainless Steel	
Weight	14/16 kg	15/17 kg
Power	2 KW	
Power Supply	220 V, 50 Hz	

AP11 PORTABLE AUTOCLAVE

Fully stainless steel structure.
Hand wheel type of quick-open door structure.
Automatic microcomputer.
Digital display of working status,touch type key.
Automatically shut off with beep reminding after sterilization.
Electric heated.
Easy to operate,safe and reliable.



SPECIFICATIONS

Model	AP115	AP116
Capacity	18 L	24 L
Function	Electric heated	
Sterilization Temperature	126°C	
Heat Average	≤1°C	
Working Pressure	0.14-0.16Mpa	
Maximum Working Pressure	0.165 Mpa	
Timer Range	0-99min	
Chamber Dimension	280×260mm	270×500mm
Overall Dimension (LxWxH)	440×420×630 mm	440×420×750 mm
Chamber Material	Stainless Steel	
Weight	12/14 kg	14/15 kg
Power	2 KW	
Power Supply	220 V, 50 Hz	

LABSTAC

LABSTAC LTD

Kemp House 152 – 160 City Road, London, EC1V 2NX, United Kingdom
Email: contact@labstac.com | Website: www.labstac.com