

Model Q30.195.086.WD



| Dimensions | |
|---|---------------------------------|
| Width (external) | 864 mm |
| Depth (external) | 620 mm |
| Height (external) | 1947 mm |
| Width (internal) | 750 mm |
| Depth (internal) | 519 mm |
| Height (internal) | 1626 mm |
| The available internal dimensions can vary depending on | the interior equipment package. |

| Weight / Load | |
|---------------------------------------|-----------|
| Weight without interior equipment | 195 kg |
| Distributed load | 568 kg/m² |
| Maximum load | 600 kg |
| | |
| Ventilation | |
| Extraction air | 75 DN |
| minimum exhaust air quantity 10 times | 6 m³/h |
| Pressure drop inside the cabinet | 10 Pa |

anthracite grey

Warning yellow

textured

RAL 1004

Colouring / Surface finish

Door / Drawer colour code

Body colour

Body surface finish

Door / Drawer colour

| Door / Drawer surface finish | textured |
|------------------------------|----------|
| General Information | |
| Number of doors | 1 |
| Door opening angle | 90.00° |
| Depth with open doors | 1394 mm |
| Interiour grid dimension | 32 mm |
| Entry width transport base | 788 mm |
| Entry height transport base | 90 mm |
| Customs tariff number | 94032080 |



















Safety storage cabinet Q-CLASSIC-30 Model Q30.195.086.WD, body colour anthracite grey, with wing door in warning yellow (RAL 1004)

Safe and approved storage of flammable hazardous substances in working areas

Function / construction:

- Robust construction and longevity: triple hinged door, cabinet body made of melamine resin and flame retardant special plates, safety elements assembled outside the storage compartment for increased protection against corrosion, doors with metal front as well as scratch-and impact-resistant surface, easy to clean
- Easy handling with comfort: door stops in any position, self-closing in the event of fire
- **No unauthorised use:** door lockable with profile cylinder (integration in an existing locking system possible)
- Easy transport: integrated transport base with removable, optional base cover or adjusting aids with base cover
- **Ventilation:** integrated air ducts ready for connection (DN 75) to a technical exhaust system

Front view Side view





