



P/N [O-OMISC-PTF]

## A ONE OF A KIND INNOVATIVE ORGAN-ON-A-CHIP PLATFORM

Omi is an one of a kind, **innovative automated platform** that allows to **reproduce microphysiological behavior of organs** inside **microfluidic chips**. Its versatility allows to interface with any type of chips to sustain different **cell culture types** or **organ-on-chip models** (Cut-on-chips, skin-on-chip...). This platform can be used in biological environments such as **in incubator without power supply needed** (it operates on battery).

Totally **compact and transportable**, it can be positioned **under a microscope** to observe in real time cell growth during experiment. The connection to a **cloud** allows also to **monitor Omi remotely** on a computer or using a tablet.



### KEY FEATURES



#### TRANSPORTABLE AND COMPACT

Platform that easily fits into an incubator



#### EASY TO USE

Device made for beginners or advanced OOC researchers



#### AVOID COMPLEX SET-UPS

With this fully integrated platform



#### EASY AND INTUITIVE MULTIPLEXING

For double channel chips by connecting two Omis together



#### AVOID CONTAMINATION DURING THE EXPERIMENTS

Inject or withdraw samples without disconnecting the chip



#### PERFORM ANY CUSTOMIZED PROTOCOL

That combine perfusion, recirculation, injection or sampling with any chip design



#### SAVE TIME AND AUTOMATE PROTOCOLS

With user friendly touch screen interface



#### CONTROL AND MONITOR REMOTELY

Your experiments and data thanks to the web interface and remote tablet.


# TECHNOLOGY

Omi can perform, **customize and automate** any protocol that includes simple **perfusion, recirculation, sampling** and **injection**. It can meet the needs of those just starting in the microfluidics field as well as advanced **organ-on-chip** researchers who seek **automation and reproducibility**.

With this **versatile and autonomous** human organ-on-chip platform, users can perform **long term cell culture** under flow to generate **controlled shear stress** conditions. Its **two hour autonomy** battery and **Wifi connectivity** ensures **easy and intuitive monitoring** and smooth **transportation** from an **incubator to a microscope** to perform live cell imaging while maintaining cell perfusion.

Omi can be used in single or dual perfusion mode to perform either single channel perfusion for blood vessel reproduction for example or co culture for liquid/liquid interfaces for gut on chip or blood brain barrier reproduction by synchronizing two Omis with one organ on chip.

The disposable sterile cartridge **prevents contamination** between experiments and the universal adaptor allows the connection of the platform to **any microfluidic chip design**.



# PERFORMANCE

## PERFUSION

Omi gives the possibility to perfuse up to 4 mL of many types of liquids such as cell culture media for a long period of time in a controlled and reproducible way. The stability and precision of the perfusion allow control of the shear stress throughout any experiment.

## RECIRCULATION


Omi allows a unidirectional recirculation of medium while maintaining a constant flow rate for a long period of time.

## SAMPLING

Sample up to 4 mL of soluble factors secreted in the culture medium for analysis or imagery.

## INJECTION

Omi allows the injection up to 4 mL of fresh medium during the experiments.



# SPECIFICATIONS

## OMI DEVICE AND TABLET

PERFORMANCE	
Flow rate control	From 1 µL/min to 1 mL/min
Maximum pressure	800 mbar maximum
Flow rate precision (below 10µl/min)	0.5 µl/min
Flow rate precision (above 10µl/min)	5% mv (measured value)
Fluids reservoir volume (4)	4 mL
Min perfusion volume	From 1 mL to 4 mL
Min buffer required in reservoir RI (recirculation inlet)	2.5 mL
Min volume injected in reservoir (I)	1 mL
MECHANICAL SPECIFICATIONS	
Wetted materials	Polycarbonate, medical grade MVQ silicone, EPDM, PEEK, FEP, PPS, medical grade stainless steel
Dimensions	190 x 120 x 60 (mm)
Weight	757 g
Power supply voltage	24 V DC
Max energy consumption	12 W
Max current requirement	0.5 A
Operating temperatures	15-40 °C
Gas input pressure	Atmospheric pressure
Gas input composition	Dry 2 µm-filtered air, nitrogen

When reservoirs are filled to the minimum (1 mL per reservoir), the minimum additional volume that can be recirculated is 250 µL

### TABLET\*

P/N	O-OMI-TAB
Product	Samsung Galaxy Tab S6 Lite 10.4" - 64 Go Ref SM-P610

\*Our OMI application can be used on any tablet model but Fluigent does not ensure the same performances as with our tablet.

Android version must be above version 9.0 (API level 28). A Google account is necessary to access the Google Play Store and access the application. To enable a Bluetooth connection, GPS must be activated (Android requirements) and users must accept to give the following rights to the Omi application (asked upon starting Omi application for the first time):

- Allow to access device location data
- Allow to use photos and videos
- Allow to access user folders

## DISPOSABLES

### UNIVERSAL ADAPTATOR

Dimensions	68 x 26 x 19.4 (mm)
Weight	13 g
Materials	Medical grade polycarbonate

### CARTRIDGE

Dimensions	80 x 60 x 36 (mm)
Weight	56 g
Wetted materials	Medical grade polycarbonate and MVQ silicone*
Working Fluid	Water based solutions*, IPA, Ethanol
Cleaning	Isopropanol, 80%/20% v/v water ethanol solution
Channels inner diameter	250 µm

\*Check the material compatibility of the used solutions with the wetted materials

### TUBING

Material	FEP (provided), but other materials possible depending on the connector
ID	250 µm (provided), but other can be used depending on the application
OD	1/16" (provided), but other if used with a compatible ¼-28 flat bottom connector

# DETAILED CONTENT

## OMI'S PACKAGES

OMI SINGLE CHANNEL PLATFORM [O-OMISC-PTF]		
P/N	Content	Quantity
O-OMI-SA	OMI Stand alone	1
O-OMI-TAB	OMI tablet	1
O-OMI-CART	Set of 3 Cartridges (sterile package) :	1
O-OMI-LRCC	Set of 3 Low resistance adaptors (sterile package) :	1
O-OMI-HRCC	Set of 3 High resistance adaptors (sterile package) :	1

OMI DOUBLE CHANNEL PLATFORM [O-OMIDC-PTF]		
P/N	Content	Quantity
O-OMI-SA	OMI Stand alone	2
O-OMI-TAB	OMI tablet	1
O-OMI-CART	Set of 3 Cartridges (sterile package) :	2
O-OMI-LRCC	Set of 3 Low resistance adaptors (sterile package) :	2
O-OMI-HRCC	Set of 3 High resistance adaptors (sterile package) :	2

OMI STAND ALONE [O-OMI-SA]		
P/N	Content	Quantity
O-OMI-DEV	OMI device	1
O-OMI-AF-CTK	OMI air filter and pneumatic kit	1
O-OMI-CTK	OMI tubing and fitting kit	1
O-OMI-SK O-OMI-LU	Power supply kit (socket depends on the region)	1

## KITS

POWER SUPPLY KIT [O-OMI-SK]	
Content	Quantity
Power supply (24V 1,75A)	1
Power cable - EUR - Little	1
DC power chord male-male (5.5x2.5mm, 30cm, white, 24AWG)	1

OMI AIR FILTER AND PNEUMATIC KIT [O-OMIAF-CTK]	
Content	Quantity
Lueur male big tube (white)	3
Luer lock mâle blanc to barb (1.6 mm)	3
Syringe Filters (13 mm 1.2 µm)	3
TYGON (4.8 mm OD 1.6 mm ID)	2 m
Pneumatic tube (4 mm OD)	2 m

OMI TUBING AND FITTING KIT [O-OMI-CTK]	
Content	Quantity
Fittings 1/4-28 xp235 with integrated ferrule	8
FEP Tubing (1/16" OD x .010" Natural 50ft)	1 m
Tube Cutter	1

## CERTIFICATION

The Omi device is CE and RoHS  
compliant FLUIGENT SA is ISO 9001  
certified since 2010



## SUPPORT & CONTACT

### FLUIGENT SA

O'kabé bureaux  
67 avenue de Fontainebleau  
94270 Le Kremlin-Bicêtre  
FRANCE  
[www.fluigent.com](http://www.fluigent.com)  
+33 1 77 01 82 68

### TECHNICAL SUPPORT

[support@fluigent.com](mailto:support@fluigent.com)  
+33 1 77 01 82 65

### GENERAL INFORMATION

[contact@fluigent.com](mailto:contact@fluigent.com)



Ver. Mar 2023