

Data Sheet

BCP- H_2

Advantages

- > reasonably priced
- > in-situ measurement
- > low maintenance
- > independent from gas flow
- > direct integration in gas pipes possible
- > no gas cooler, pumps or valves necessary
- > easy to use



Application areas

- > chemical industry
- > biogas production
- > agriculture
- > algal hydrogen production



**Hydrogen sensor BCP- H_2
for in-situ measuring**

Data Sheet

BCP- H_2

Sensor	BCP-H_2	
Measuring principle	Thermal conductivity detector	
Concentrations ranges	H ₂ : 0 - 10 Vol.%, 0 - 50 Vol.%, 0 - 100 Vol.%*	
Accuracy	< 0.2% FS* ± 3% reading **	
Drift	< ± 2% reading / year	
Temperature ranges	15 - 40 °C 30 - 55 °C -25 - 55 °C*	59 - 104 °F 86 - 131 °F -13 - 131 °F*
Pressure range	0.8 - 1.3 bar/11.6 - 18.85 psi absolute pressure*	
Housing	Aluminum (IP65)	PA
Dimension mm Dimension inch Weight	100 x 131 x 118 (W x D x H) 3.94 x 5.16 x 4.64 (W x D x H) 900g (1.98lb)	80 x 130 (D x H) 3.15 x 5.12 (D x H) 350g (0.77lb)
Cross sensitivity	The BCP- H_2 provides the best measurement results in binary gas mixtures. For other gas mixtures please consult us for advice.	
Internal sensor temperature	70 °C (158 °F)	
Materials in contact with gas	Steel 1.4571, Viton, LPCVD silicon nitride	
Lifetime of sensor element	approx. 3 years	

General		
Mechanical connection	G 1¼", GL 45, Tri-Clamp SMS38, hose connection 4 - 12 mm, etc.	
Power Supply	12 - 24 V, 1A	
Output	RS 232, 4 - 20 mA, RS 485***, Ethernet***, USB***	
Storage	0 °C - +60 °C	32 °F - 140 °F
	< 75% RH non condensing	
Maintenance	1-point calibration once per month. Optional factory calibration once a year.	
Remarks	Don't use in explosive environments.	

*others on request **full scale ***optional

