

Thermo Scientific TSQ Quantiva Triple-Stage Quadrupole Mass Spectrometer

Extreme quantitative performance
with unprecedented ease

- Extreme quantitative performance through Thermo Scientific™ Active Ion Management (AIM™) technology
- Attogram sensitivity
- Ultrafast selected-reaction monitoring enables quantification of more compounds in less time
- Robustness and reliability that is unprecedented in a research-grade triple quadrupole mass spectrometer
- Close integration with application-specific software ensures maximum productivity
- Simple method development and easy operation



The Thermo Scientific™ TSQ Quantiva™ triple-stage quadrupole mass spectrometer exceeds the most stringent analytical requirements. With AIM technology, the TSQ Quantiva MS achieves unrivaled LODs and LOQs and provides unsurpassed ultra-low-level quantitation of complex and difficult-to-run samples. This extreme analytical performance doesn't come at the cost of complexity or

lack of durability; breakthrough software and hardware make operation far easier and more reliable than in previous-generation triple quadrupoles. Close integration with application-specific software ensures maximum productivity. The TSQ Quantiva MS helps users spend more time thinking about their analyses and less time worrying about instrument setup and operation.

Thermo
SCIENTIFIC

Hardware Features

Thermo Scientific™ Ion Max NG™ API Source

- Automatic connection of all gases and voltages on installation simplifies operation and improves reliability
- Automatic source recognition simplifies use and data logging
- Sweep gas reduces chemical noise
- Enhanced exhaust port efficiently removes solvent vapor, improving uptime and reducing chemical noise
- Flexible X, Y, and Z positioning for all ionization probes maximizes performance
- Optimal 60 degree spray angle
- Interchangeable HESI and APCI ionization probes
- Dual-mode HESI and APCI capability

High-Capacity Transfer Tube

The high-capacity transfer tube (HCTT) allows more ions into the vacuum system for improved sensitivity while still providing great desolvation.

Active Ion Management Ion Optics

AIM technology maximizes ion transmission, eliminates major sources of noise, and precisely isolates analytes to achieve extreme quantitative performance.

Electrodynamic Ion Funnel

The electrodynamic ion funnel (EDIF) efficiently captures ions as they leave the transfer tube. Its broad transmission curve reduces ion losses, increasing sensitivity. The EDIF also reduces in-source fragmentation.

Ion Beam Guide

The ion beam guide, with its neutral blocker, stops neutrals and high-velocity clusters, keeping the ion optics cleaner, reducing noise, and increasing sensitivity.

HyperQuad Quadrupole Mass Filter (Q1 and Q3)

Thermo Scientific™ HyperQuad™ quadrupole mass filters with 6 mm field radius and asymmetric RF drive increase ion transmission and sensitivity. Resolution up to 0.2 FWHM enables better selected-reaction monitoring.

Active Collision Cell (Q2)

The high-pressure argon-filled collision cell produces efficient fragmentation for high sensitivity. An axial DC field speeds ion transits, yielding up to 500 SRMs/s with zero cross talk.

Detector

- Dual-mode discrete-dynode detector increases sensitivity by operating in pulse-counting mode when ion flux is low and analog mode when ion flux is high
- Six orders of dynamic range provide high-confidence quantitation

Vacuum System

- Four-stage differentially pumped vacuum manifold
- Advanced triple-inlet turbomolecular pump integrated with the vacuum manifold
- Dual rotary vacuum pump configuration


Integrated Divert Valve and Syringe Pump

Fully automated data system control of the divert valve enables switching the solvent front, gradient end point, or any portion of the HPLC run to waste.

Optional Ion Sources

- Thermo Scientific™ EASY-Max NG™ ion source provides high performance with minimal adjustments
- Thermo Scientific™ EASY-Spray NG™ ion source is designed for maximum nanoelectrospray performance with no need for adjustments
- Thermo Scientific™ Nanospray Flex NG™ ion source is designed for ultimate nanoelectrospray performance with complete flexibility of column selection

Figure 1. TSQ Quantiva ion optics



Software Features

Data System

- High-performance PC with Intel® microprocessor
- High-resolution LCD color monitor
- Microsoft® Windows® 7 operating system (64 bit)
- Microsoft Office 2010 software

Standard MS Software

- Thermo Scientific™ Xcalibur™ processing and instrument control software
- Tune editor for system calibration, diagnostics, and manual data acquisition
- Method editor with comprehensive application-specific template library and drag-and-drop user interface to facilitate method development
- Automated optimization of all instrument parameters, including gas pressures and collision energy, within an experiment
- Direct control of multiple vendors' LC systems and autosampler configurations through Xcalibur software
- Foundation of shared, state-of-the-art software makes it easier to transfer methods between next-generation instruments

Scan Functions

- Highly sensitive full-scan MS in Q1 or Q3
- Selected-ion monitoring (SIM) in Q1 or Q3
- Selected-reaction monitoring (SRM) with up to 30,000 SRMs definable and up to 500 SRMs/s
- High-resolution (0.2 Da) selected-reaction monitoring
- Product ion scanning
- Precursor ion scanning
- Neutral-loss scanning
- Reverse energy ramp MS/MS spectra (RER) gives information-rich MS/MS spectra for solid compound identification
- Polarity switching capabilities

Optional Application-Specific Software

- Thermo Scientific™ LCQUAN™ quantitation software supports 21 CFR Part 11 compliance
- Thermo Scientific™ TraceFinder™ software simplifies method development and routine analysis in food safety, environmental, clinical research, and forensic toxicology laboratories
- Thermo Scientific™ Pinpoint™ software automates peptide quantitation applications
- Thermo Scientific™ Mass Frontier™ spectral interpretation and classification software for the identification of unknowns

Performance Specifications

Sensitivity

Positive Electrospray (HESI) at Resolution 0.2 Da FWHM

A 2 µL injection of a 500 fg/µL reserpine solution on a Thermo Scientific™ Hypersil GOLD™ aQ 20 x 2.1 mm 1.9 µm particle packed column at a flow rate of 300 µL/min 30:70:0.02 water/methanol/formic acid will produce a minimum signal-to-noise ratio of 100,000:1 for the transition of the protonated molecule at m/z 609.3 to the fragment ion at m/z 195.1 when operated in selected-reaction monitoring (SRM) mode with Q1 and Q3 resolution set to 0.2 and 0.7 Da FWHM respectively.

Mass Range

m/z 10-1850

Resolution

Q1 and Q3 adjustable to 0.2 Da peak width (FWHM) across the entire mass range

Scan Rate

15,000 amu/second at a resolution of 2 FWHM

500 SRMs/second (for any resolution from 0.2 through 2.0 FWHM)

Mass Stability

Mass assignment will be within ± 0.05 Da over a 24 hour period. The laboratory room temperature must be maintained between 18–27 °C (65–81 °F). The room temperature may not change by more than 5 °C (9 °F) during this period.

Installation Requirements

Power

- Three 230 Vac $\pm 10\%$, 50/60 Hz at 16 A minimum
- Four 120 Vac $+6-10\%$, 50/60 Hz at 20 A or four 230 Vac $\pm 10\%$, 50/60 Hz at 13 A
- Earth ground hardwired to main panel
- Free from voltage variations above or below the recommended operating range

Gas

- Collision gas: 99.995% pure Argon
- Collision gas supply pressure: 135 \pm 70 kPa (20 \pm 10 psig)
- Sheath/aux/sweep gas: 99% pure Nitrogen
- Sheath/aux/sweep gas supply pressure: 690 \pm 140 kPa (100 \pm 20 psig)
- Maximum sheath gas consumption: \approx 20 L/min

Environment

- Functional temperature range: 15–27 °C (59–81 °F)
- Optimal temperature range: 18–21 °C (65–70 °F)
- Heat output: 1550 W (5400 Btu/h)
- Total system heat output: 4420 W (15,380 Btu/h)
- Particulate matter: <3,500,000 particles per cubic meter of air (<100,000 particles of >5 µm diameter per cubic foot of air)
- Relative humidity: 20% to 80%, without condensation
- Floors must be free of vibration

Dimensions

Size

- TSQ Quantiva MS¹: 680 × 760 × 840 mm (h, w, d – 27 × 30 × 33 in)
- Oerlikon® SV 65 forepump: 270 × 320 × 489 mm (h, w, d – 10 × 13 × 19 in)

Weight

- TSQ Quantiva MS: 125 kg (275 lb)
- Oerlikon® SV 65 forepump: 52 kg (115 lb)

1. Includes the divert/inject valve

For Research Use Only. Not for use in diagnostic procedures.

www.thermoscientific.com

©2013 Thermo Fisher Scientific Inc. All rights reserved. ISO is a trademark of the International Standards Organization. Intel is a registered trademark of Intel Corporation. Microsoft and Windows are registered trademarks of Microsoft Corporation. Oerlikon is a registered trademark of OC Oerlikon Corporation AG. All other trademarks are the property of Thermo Fisher Scientific Inc. and its subsidiaries. Specifications, terms and pricing are subject to change. Not all products are available in all countries. Please consult your local sales representative for details.



Thermo Fisher Scientific,
San Jose, CA USA is
ISO 9001:2008 Certified.

Africa-Other +27 11 570 1840	Europe-Other +43 1 333 50 34 0	Japan +81 45 453 9100	Spain +34 914 845 965
Australia +61 3 9757 4300	Finland/Norway/Sweden +46 8 556 468 00	Latin America +1 561 688 8700	Switzerland +41 61 716 77 00
Austria +43 1 333 50 34 0	France +33 1 60 92 48 00	Middle East +43 1 333 50 34 0	UK +44 1442 233555
Belgium +32 53 73 42 41	Germany +49 6103 408 1014	Netherlands +31 76 579 55 55	USA +1 800 532 4752
Canada +1 800 530 8447	India +91 22 6742 9434	New Zealand +64 9 980 6700	
China +86 10 8419 3588	Italy +39 02 950 591	Russia/CIS +43 1 333 50 34 0	
Denmark +45 70 23 62 60		South Africa +27 11 570 1840	

PS63845_E 07/13M

Thermo
SCIENTIFIC
Part of Thermo Fisher Scientific