



lab disc pattern

超薄磁力搅拌器，采用最先进的磁力线圈技术，内部无运动部件，无磨损。为了确保更好的搅拌，每隔30秒自动改变搅拌转向。

- 高IP保护等级(IP 65)
- 盘面和外壳采用耐化学腐蚀材料精制而成
- 防滑安全支脚

选配件: IKAFLON® 10 Set (5 Pcs) round PTFE-coated Magnetic stirring bars, IKAFLON® 9 Set (5 Pcs) crown PTFE-coated Magnetic stirring bars, IKAFLON® 15 Set (5 Pcs) round PTFE-coated Magnetic stirring bars, IKAFLON® 20 Set (5 Pcs) round PTFE-coated Magnetic stirring bars, IKAFLON® 25 Set (5 Pcs) round PTFE-coated Magnetic stirring bars, IKAFLON® 30 Set (5 Pcs) round PTFE-coated Magnetic stirring bars, IKAFLON® glass 25 Set (5 Pcs) round Magnetic stirring bars, IKAFLON® glass 30 Set (5 Pcs) round Magnetic stirring bars, IKAFLON® 15 Set (5 Pcs) power SmSo PTFE-coated Magnetic stirring bars, IKAFLON® 30 Set (5 Pcs) power SmSo PTFE-coated Magnetic stirring bars, IKAFLON® 25 Set (5 Pcs) slide round PTFE-coated Magnetic stirring bars, IKAFLON® 30 Set (5 Pcs) slide round PTFE-coated Magnetic stirring bars, IKAFLON® 20 Set (5 Pcs) ellipse PTFE-coated Magnetic stirring bars, IKAFLON® 25 Set (5 Pcs) ellipse PTFE-coated Magnetic stirring bars, IKAFLON® 30 Set (5 Pcs) ellipse PTFE-coated Magnetic stirring bars, IKAFLON® 10 Set (5 Pcs) cross PTFE-coated Magnetic stirring bars, IKAFLON® 20 Set (5 Pcs) cross PTFE-coated Magnetic stirring bars, IKAFLON® 25 Set (5

技术参数	
搅拌点位数目	1
每个搅拌点位最大搅拌量 (H2O) [l]	0.8
电机输入功率 [W]	5
电机输出功率 [W]	3
速度范围 [rpm]	15 - 1500
搅拌子最大长度 [mm]	25
工作盘材质	聚酯薄膜
工作盘外形尺寸 [mm]	Ø 100
外形尺寸 [mm]	117 x 12 x 180
重量 [kg]	0.3
允许环境温度 [° C]	5 - 40
允许相对湿度 [%]	80
DIN EN 60529 保护方式	IP 65
电压 [V]	100 - 240
频率 [Hz]	50/60
仪器输入功率 [W]	5
订货号	3765000

Pcs) cross PTFE-coated Magnetic stirring bars, IKAFLON® 30 Set (5 Pcs) cross PTFE-coated Magnetic stirring bars,
TRIKA® 25 Set (5 Pcs) PTFE-coated Magnetic stirring bars, RSE 搅拌子移出棒