



color squid IKAMAG® red flag

最新改进的小型磁力搅拌器。

New: 转速数字显示 (LED)

New: 电子控制马达能力更强

New: 更高的转速范围 : 0-2,500 rpm

New: 最大搅拌量1升

- 由于采用了玻璃盘面以及TPC-ET化学合成材料精制而成，具有良好的耐化学腐蚀性
- 可循环利用材料精制而成

选配件: IKAFLON® 10 Set (5 Pcs) round PTFE-coated Magnetic stirring bars, IKAFLON® 9 Set (5 Pcs) crown PTFE-coated Magnetic stirring bars, IKAFLON® 15 Set (5 Pcs) round PTFE-coated Magnetic stirring bars, IKAFLON® 20 Set (5 Pcs) round PTFE-coated Magnetic stirring bars, IKAFLON® 25 Set (5 Pcs) round PTFE-coated Magnetic stirring bars, IKAFLON® 30 Set (5 Pcs) round PTFE-coated Magnetic stirring bars, IKAFLON® glass 25 Set (5 Pcs) round Magnetic stirring bars, IKAFLON® glass 30 Set (5 Pcs) round Magnetic stirring bars, IKAFLON® 15 Set (5 Pcs) power SmSo PTFE-coated Magnetic stirring bars, IKAFLON® 30 Set (5 Pcs) power SmSo PTFE-coated Magnetic stirring bars, IKAFLON® 25 Set (5 Pcs) slide round PTFE-coated Magnetic stirring bars, IKAFLON® 30 Set (5 Pcs) slide round PTFE-coated Magnetic stirring bars, IKAFLON® 20 Set (5 Pcs) ellipse PTFE-coated Magnetic stirring bars, IKAFLON® 25 Set (5 Pcs) ellipse PTFE-coated Magnetic stirring bars, IKAFLON® 30 Set (5 Pcs) ellipse PTFE-coated Magnetic stirring bars, IKAFLON® 10 Set (5 Pcs) cross PTFE-coated Magnetic stirring bars, IKAFLON® 20 Set (5 Pcs) cross PTFE-coated Magnetic stirring bars, IKAFLON® 25 Set (5 Pcs) cross PTFE-coated Magnetic stirring bars, IKAFLON® 30 Set (5 Pcs) cross PTFE-coated Magnetic stirring bars, TRIKA® 25 Set (5 Pcs) PTFE-coated Magnetic stirring bars, RSE 搅拌子移出棒

技术参数

搅拌点位数目	1
每个搅拌点位最大搅拌量 (H2O) [l]	1
最大搅拌量 (H2O) [l]	1
电机输入功率 [W]	3
电机输出功率 [W]	2
转速显示	LED
速度范围 [rpm]	0 - 2500
搅拌子最大长度 [mm]	30
工作盘外形尺寸 [mm]	Ø 115
外形尺寸 [mm]	145 x 45 x 160
重量 [kg]	0.54
允许环境温度 [°C]	5 - 40
允许相对湿度 [%]	80
DIN EN 60529 保护方式	IP 54
RS 232接口	不
模拟输出	不
电压 [V]	100 - 240
频率 [Hz]	50/60
仪器输入功率 [W]	4
DC Voltage [V=]	12
Current consumption [mA]	300
订货号	4175400