

红外相机观察仪



新势力光电供应**红外相机观察仪**，光谱范围涵盖 400-2200nm，电子取景器模块可供选择。**红外相机观察仪**应用广泛，包括：激光、通讯、生物医疗等领域。

Model	85720/85700	85726/85706
Spectral sensitivity	400-1800nm	400-2200nm
Regions displayed	VIS, Near-IR, Min-IR	VIS, Near-IR, Min-IR
Peak sensitivity	600nm	600nm
Focal range	4" to infinity	4" to infinity
Detector	25mm high performance infrared vidicon	25mm high performance infrared vidicon
Standard lens	"C" mount 25mm, f/1.4 with manual iris	"C" mount 25mm, f/1.4 with manual iris
Gain	selectable, auto gain and 4 fixed values	selectable, auto gain and 4 fixed values
Signal to noise ratio	68dB	68dB
Horizontal resolution	up to 700 TV lines	up to 700 TV lines
External connection	RS-170 video output via BNC connector	RS-170 video output via BNC connector
Dimensions	110.3×111.2×216.4mm ³	110.3×111.2×216.4mm ³

www.NewOpto.com

NewOpto Technology Corporation Limited

7F, Building D, Cambridge Community, No.789 Shenhua Road, Hangzhou, China 310030

Phone: +86-571-85152711 Fax: +86-571-85152722 Email: Sales@NewOpto.com