

## 便携式pH计和电导率仪



PHB-1便携式pH计



PHB-2便携式pH计



PHB-4便携式pH计



DDB-11A便携式电导率仪



- 智能型单芯片设计
- 低电压显示, 15min自动关机
- 自动校正, 有温度补偿
- 专用手提箱, 内置校正溶液

型号名称	PHB-1便携式pH计	PHB-2便携式pH计	PHB-4便携式pH计	DDB-11A便携式电导率仪
测量范围	pH: 0~14.00 pH mV: ±1999mV	pH: 0~14.0 pH	pH: 0~14.00 pH mV: ±1999mV 温度: 0~80 °C	0 ~ 2×10 <sup>5</sup> µS/cm
分辨率	0.01 pH, 1mV	0.1pH	0.01 pH, 1mV/0.1°C	0.1/1µS/cm; 0.01/0.1mS/cm
精度	pH: ±0.01 pH mV: ±0.1%FS	±0.1 pH	pH: ±0.01 pH mV: ±0.1%FS 温度: ±1°C	± 1.0%FS
温度补偿	0~ 80 °C (手动)		0~80 °C (自动)	0~50°C (手动)
电极	201-A塑壳pH复合电极	201-C塑壳pH复合电极	201B-S塑壳pH三复合电极	2301-C电导电极 (K=1)
校正溶液	pH4.00, pH6.86, pH9.18各一瓶/50mL			1408 µS/cm一瓶/50mL
电源	9V叠层电池			
尺寸及重量	168×43×26(mm) / 170 g			