



Portable Brix Meter

Check-Brix

NEW

RA-250HE



You see sweetness within 2 seconds!

Easy to maintain with washing by water!

Measurement is applicable to anywhere!

No longer necessary to read graduation due to digital display!

Actual Size

*For measurements of
sweetness of fruits, vegetables,
drinks and foods!*

1~2 Drops



Sample

Accurate meas.
with 0.1mL sample

Quick Meas.



Quick meas. within
2 seconds

Waterproof



Protected against
water jets

Backlight



LCD with backlight

30,000 Times



Long battery life

Anywhere



Outdoor or Indoor?
It doesn't matter

KYOTO ELECTRONICS

Typical sample and Common Brix%

Category	Samples	0	10	20	30	40
Fruit	Oranges		█			
	Pears		█			
	Tomatoes		█			
	Apples		█			
	Melons		█			
	Strawberries		█			
	Peaches		█			
	Grapes		█			
	Water melons		█			
	Cherries		█			
Fruit juice Soft drink	Fruit juices		█			
	Nectars		█			
	Carbonated beverages		█			
Tomato processed food	Tomato juices		█			
	Tomato puree		█			
	Tomato ketchup		█			
Dairy goods	Lactic acid beverages		█			
	Milk		█			
Coffee	Coffee		█			
Seasoning	Soy source		█			
	Worcestershire sauce		█			
Others	Canned fruit		█			

Features

- Sugar content (Brix%) is digitally displayed
- Wide measuring range (0 - 60 Brix%)
- High resolution (0.1 Brix%)
- Temperature Compensation Function
- Easy-operation — just apply sample
- High-performance at a Low price
- Light-weight and compact handheld size
- Easy-to-read LCD with backlight
- Battery operated
- Reliable water proof structure (IP 65 compliant)
- Automatic power off

Specifications

Resolution	0.1Brix%
Precision	±0.2Brix%
Measuring range	0 ~ 60 Brix%
Temperature range	10°C ~ 70°C
Temperature compensation	Built-in
Display	Brix% (With backlight)
Power source	Two AAA dry cells (Alkaline)
Battery life	30,000 measurements (Alkaline cells w/o backlight)
Dimension	43(W) x 26(D) x 170(H) mm
Weight	Approx. 100g (Excluding dry cells)
Dust/Water proof class	IP 65 (Dust-tight and protected against water jets)

- Accurate measurement with a small volume*
- Digital display with the touch of a button

* Measurement by 1-2 drops (0.1mL)

Directions for use

- ① Drip 1 or 2 drops of sample on prism.

- ② Press [Meas.] key once. Measurement is completed.

- ③ The unit can be washed by water.



KEM
KYOTO ELECTRONICS
MANUFACTURING CO.,LTD.

Overseas Division : 8-3 Niban-cho Chiyoda-ku TOKYO 102-0084, JAPAN

Fax : +81-3-3237-0537, Phone : +81-3-3239-7333

URL : <http://www.kyoto-kem.com>



Distributed by :

Specifications and design subject to change for improvements without notice. printed in Japan.

42IK53B